



Dear Friends and Partners,


We are pleased to present the new Middle East Shortform catalogue 2012.



Hager stands for sustainability and our E3 Initiative is an excellent example of this. Fully aware of our responsibility to both society and the environment, we are proud to make a contribution to the better use of the limited available resources. It is a belief that plays a vital role in all our new developments. The three Es, by the way, stand for the categories of "ethics, environment and eco-efficiency". And behind each category there is an actual catalogue of measures to which Hager is expressly committed, measures including: Investors in People certification (IIP), an employee development programme; the United Nations Global Compact initiative, which the Hager Group joined in 2007; and the environmental standard ISO 14000, to which most of our sites are already certified to. In this respect, ecological development and production technologies are given as much careful consideration as to the products themselves that make a contribution to make better use of the resource electricity.

Innovation, customer proximity, simplicity and reliability are the very basis of the Hager brand. We keep in close contact with our customers, regularly surveying their wishes and needs before incorporating that feedback into the development of our new systems. The same applies to this catalogue which we have designed for you as a practical tool.

Why not have a browse and find out for yourself?

Best regards,  
Daniel Hager







# The partner for smart solutions you can trust

Hager is a full range supplier of electrical installation systems for building, residential and commercial properties. For decades, Hager has been synonymous with an extensive and complete offering. Highest quality, cutting edge products, modularity, ease of installation, ease of use, excellent service and sophisticated design are the features that distinguish Hager.

## Hager: a brand meeting your expectations

As a specialist in

- power distribution,
- cable management and room connection systems,
- switch programmes and smart building automation as well as safety technology such as alarm systems, smoke detectors and motion detectors.

Hager the supplier for professionals is a synonym for top quality and innovative technology, as well as good customer relations and reliability. All of which make Hager the partner for smart solutions, you can trust.

## New ideas for the customers' benefit

Innovations and the systematic enhancement of the products and systems are key features of the Hager brand. It has always been our goal to use new designs and improvements to stay ahead of developments.


The use of innovations and new technologies at Hager is always customer driven. Every year, Hager evaluates thousands of customer contacts, resulting in detailed knowledge of its customers' needs in order to work efficiently and successfully. Based on this knowledge, Hager develops the innovative solutions that are so characteristic for the Hager brand. Ease of installation, ease of use, intuitive user interfaces, modularity and durability are brand values that guarantee highest quality throughout in Hager systems.

65 percent of the products are less than three years old. This high degree of innovation enables the users to meet various new challenges effectively. The strong demand for innovations and enhancements is a good indicator for the customer oriented policy of the Hager brand also resulting in a high turnover at wholesalers.

## A flourishing group

Hager belongs to the Hager Group, which is a family owned business with a more than fifty year tradition. As a global player, the company has about 11,400 employees and a turnover of more than 1.55 billion Euro in 2011.

[www.hager.ae](http://www.hager.ae)



# Hager regional support Middle East operations

With an objective of offering technical and commercial support to our customers in the Middle East and Near East regions, Hager group set up its 100% owned subsidiary, Hager Tehalit Systems Middle East FZE (HTSME), at Jebel Ali Free Zone in 1997.


Today Hager Middle East has a strong commercial team with expertise in sales and marketing, product management, logistics, customer service and finance. Hager Middle East has regional representation in Saudi Arabia, Kuwait and Qatar.


With an aim to provide the best solution for your distribution system, Hager Middle East has a dedicated team of qualified and professional engineers to provide advice on any design and technical application.

Hager Middle East gives special emphasis to training of customers and updation of new product launches. The training facility at Jebel Ali office stands testimony to this commitment.

Technical seminars are conducted at various locations to keep customer abreast of various product launches.

Courses are in modular format and are customized to meet individual market requirements. Hager Middle East also conducts special courses on request. These customer oriented programmes are instrumental in reinforcing the trust and quality in the Hager brand.




Air circuit breakers	p.6
 MCCBs	p.13
Load break switches	p.25
Power contactors	p.27
Thermal overload relays	p.28
Switch disconnectors (isolators)	p.29
Miniature circuit breakers	p.30
RCCBs	p.32
RCBOs	p.33
RCD add-on blocks	p.34
Fuse carriers	p.35
Fuse links	p.35
Earth leakage relays	p.36
Torroidal transformers	p.37
Modular contactors	p.38
Time switches	p.39
Twilight switches	p.40
Astronomical time switches	p.40

Delay timers	p.41
Latching relays	p.42
Push buttons	p.43
Indicator lights	p.44
Hour counters	p.44
Kilowatt hour meters	p.45
Dimmers	p.46
Motion detectors	p.47
Presence detectors	p.48
Slotted trunking system	p.49
Invicta consumer units	p.51
Invicta DIN rail distribution boards	p.51
Invicta TPN distribution boards	p.53
Invicta panel boards	p.57
Enclosed loadbreak switches	p.62
Enclosed fuse combination switches	p.63
Enclosed circuit breaker	p.64
Vector enclosures	p.65
Golf enclosures	p.65
Insulated busbars and terminals	p.66
Invicta dimensions	p.67



Air Circuit Breakers are widely used in low voltage power distribution systems of industrial, residential and commercial buildings. As the main incoming device, Hager ACBs has high dynamic and thermal stability. It not only ensures uninterrupted power supply, but also breaks reliably at high short circuit currents.

Hager ACBs are available from 800A to 4000A, in three frame sizes, with breaking capacities of 65KA, 80KA & 100KA and  $I_{cu} = I_{cs} = I_{cw}$ .



Microprocessor based protection controller units with LSI & LSIG functions.



Compact size - same height and depth across all frame sizes.




Clear indications of auxiliaries mounted inside.



Fixed and drawout interchangeability

Rated current	Breaking capacity Icu		65kA		80kA		100kA	
	pole	earth fault protection	draw-out type	fixed type	draw-out type	fixed type	draw-out type	fixed type
800 A	3	No	HWN308A3	HWN308C3	HWS308A3	HWS308C3		
		Yes	HWN308B3	HWN308D3	HWS308B3	HWS308D3		
	4	No	HWN408A3	HWN408C3	HWS408A3	HWS408C3		
		Yes	HWN408B3	HWN408D3	HWS408B3	HWS408D3		
1000 A	3	No	HWN310A3	HWN310C3	HWS310A3	HWS310C3		
		Yes	HWN310B3	HWN310D3	HWS310B3	HWS310D3		
	4	No	HWN410A3	HWN410C3	HWS410A3	HWS410C3		
		Yes	HWN410B3	HWN410D3	HWS410B3	HWS410D3		
1250 A	3	No	HWN312A3	HWN312C3	HWS312A3	HWS312C3		
		Yes	HWN312B3	HWN312D3	HWS312B3	HWS312D3		
	4	No	HWN412A3	HWN412C3	HWS412A3	HWS412C3		
		Yes	HWN412B3	HWN412D3	HWS412B3	HWS412D3		
1600 A	3	No	HWN316A3	HWN316C3	HWS316A3	HWS316C3		
		Yes	HWN316B3	HWN316D3	HWS316B3	HWS316D3		
	4	No	HWN416A3	HWN416C3	HWS416A3	HWS416C3		
		Yes	HWN416B3	HWN416D3	HWS416B3	HWS416D3		
2000 A	3	No	HWN320A3	HWN320C3	HWS320A3	HWS320C3		
		Yes	HWN320B3	HWN320D3	HWS320B3	HWS320D3		
	4	No	HWN420A3	HWN420C3	HWS420A3	HWS420C3		
		Yes	HWN420B3	HWN420D3	HWS420B3	HWS420D3		
2500 A	3	No			HWS325A3	HWS325C3		
		Yes			HWS325B3	HWS325D3		
	4	No			HWS425A3	HWS425C3		
		Yes			HWS425B3	HWS425D3		
3200 A	3	No			HWS332A3	HWS332C3	HWP332A3	HWP332C3
		Yes			HWS332B3	HWS332D3	HWP332B3	HWP332D3
	4	No			HWS432A3	HWS432C3	HWP432A3	HWP432C3
		Yes			HWS432B3	HWS432D3	HWP432B3	HWP332D3
4000 A	3	No					HWP340A3	HWP340C3
		Yes					HWP340B3	HWP340D3
	4	No					HWP440A3	HWP440C3
		Yes					HWP440B3	HWP440D3

Dimensions



H: height  
W: width  
D: depth with flat terminals

Common parameters

Rated operational voltage at 50/60 Hz	Upto 690 V AC
Rated insulation voltage at 50/60 Hz	1000 V AC
Rated impulse withstand voltage - main circuit	12 KV
Rated impulse withstand voltage - auxiliary circuit	4 KV
Suitability for isolation	Yes
Intrinsic degree of protection of breaker front	IP53
Pollution degree suitability	3
Utilization category	B
Compliance	EN60947-2, IEC60947-2, GB14048-2

Rating specific parameters

Rating specific parameters				Neutral	Unit	Symbol			
Frame							I	II	III
Rated current					A	In	800-2000A	800-3200	3200, 4000
Version							N	S	P
Rated ultimate S.C. breaking capacity	400/415VAC 50/60 Hz				kA	Icu	65	80	100
	500/550VAC 50/60 Hz				kA		55	70	85
	660/690VAC 50/60 Hz				kA		50	55	75
Rated service S.C. breaking capacity	400/415VAC 50/60 Hz				kA	Ics	100% Icu	100% Icu	100% Icu
	500/550VAC 50/60 Hz				kA				
	660/690VAC 50/60 Hz				kA				
Rated short time withstand capacity	0,5 sec				kA	Icw	65	80	100
	1 sec				kA		65	75	100
	3 sec				kA		36	50	57
Rated S.C. making capacity	400/415VAC 50/60 Hz				kA	Icm	143	176	220
	500/550VAC 50/60 Hz				kA		121	154	187
	660/690VAC 50/60 Hz				kA		105	121	165
opening time					ms		40	40	40
closing time					ms		60	60	60
Dimensions	fixed ACB	width 3P		mm	W	347	447	647	
		width 4P	100%	mm	W	447	581	847	
		depth		mm	D	355	355	355	
		height		mm	H	430	430	430	
	drawout ACB	width 3P		mm	W	347	447	647	
		width 4P	100%	mm	W	447	581	847	
		depth		mm	D	421	421	421	
		height		mm	H	433	433	433	
Mechanical life					no. of cycles	20000	15000	10000	
Frequency of operation - mechanical					cycles/hour	60	60	60	
Electrical life					no. of cycles	10000	5000	5000	
Frequency of operation - electrical					cycles/hour	40	30	20	
Pitch I/C - O/G					mm		105	105	105
Pitch	Ph-Ph			mm		100	133,3	200	
	Ph-N		100%	mm		80	100	165	
Termination width	Phase			mm		80	100	165	
	Neutral		100%	mm		80	100	165	
Weight	fixed ACB	3P		kg		39	59	86	
		4P	100%	kg		48	71	108	
	drawout ACB	3P		kg		70	88	124	
		4P	100%	kg		84	106	166	

- Technical characteristics:**

  - Standards: IEC 60947-2
  - Current rating: 800A  
1000A / 1250A / 1600A / 2000A
  - Protection controller:  
microprocessor based LSI and  
LSIG
  - Fixed and draw out version
- Breaking and short time  
withstand capacity  
(400 / 415V)  
Icu=65kA  
Ics = 100% Icu  
Icw = 65kA (1s)



HWN312B3

Designation	Rated current	Pole	Cat. ref. w/o earth fault 65kA	Cat. ref. with earth fault 65kA
Draw out circuit breaker				
	800A	3	HWN308A3	HWN308B3
	1000A	3	HWN310A3	HWN310B3
	1250A	3	HWN312A3	HWN312B3
	1600A	3	HWN316A3	HWN316B3
	2000A	3	HWN320A3	HWN320B3
	800A	4	HWN408A3	HWN408B3
	1000A	4	HWN410A3	HWN410B3
	1250A	4	HWN412A3	HWN412B3
	1600A	4	HWN416A3	HWN416B3
	2000A	4	HWN420A3	HWN420B3
Fixed circuit breaker				
	800A	3	HWN308C3	HWN308D3
	1000A	3	HWN310C3	HWN310D3
	1250A	3	HWN312C3	HWN312D3
	1600A	3	HWN316C3	HWN316D3
	2000A	3	HWN320C3	HWN320D3
	800A	4	HWN408C3	HWN408D3
	1000A	4	HWN410C3	HWN410D3
	1250A	4	HWN412C3	HWN412D3
	1600A	4	HWN416C3	HWN416D3
	2000A	4	HWN420C3	HWN420D3



## Air circuit breaker - frame II 800 to 3200 A

### Technical characteristics:

- Standards: IEC 60947-2
- Current rating: 800A / 1000A / 1250A / 1600A / 2000A / 2500A / 3200A
- Protection controller: microprocessor based LSI and LSiG
- Fixed and draw out version
- Breaking and short time withstand capacity (400 / 415V)  
Icu = 80kA  
Ics = 100% Icu  
Icw = 75kA (1s) / 50kA (3s)



HWS420B3

Designation	Rated current	Pole	Cat. ref. w/o earth fault 80kA	Cat. ref. with earth fault 80kA
<b>Draw out circuit breaker</b>	800A	3	HWS308A3	HWS308B3
	1000A	3	HWS310A3	HWS310B3
	1250A	3	HWS312A3	HWS312B3
	1600A	3	HWS316A3	HWS316B3
	2000A	3	HWS320A3	HWS320B3
	2500A	3	HWS325A3	HWS325B3
	3200A	3	HWS332A3	HWS332B3
	800A	4	HWS408A3	HWS408B3
	1000A	4	HWS410A3	HWS410B3
	1250A	4	HWS412A3	HWS412B3
	1600A	4	HWS416A3	HWS416B3
	2000A	4	HWS420A3	HWS420B3
	2500A	4	HWS425A3	HWS425B3
	3200A	4	HWS432A3	HWS432B3
<b>Fixed circuit breaker</b>	800A	3	HWS308C3	HWS308D3
	1000A	3	HWS310C3	HWS310D3
	1250A	3	HWS312C3	HWS312D3
	1600A	3	HWS316C3	HWS316D3
	2000A	3	HWS320C3	HWS320D3
	2500A	3	HWS325C3	HWS325D3
	3200A	3	HWS332C3	HWS332D3
	800A	4	HWS408C3	HWS408D3
	1000A	4	HWS410C3	HWS410D3
	1250A	4	HWS412C3	HWS412D3
	1600A	4	HWS416C3	HWS416D3
	2000A	4	HWS420C3	HWS420D3
	2500A	4	HWS425C3	HWS425D3
	3200A	4	HWS432C3	HWS432D3

## Air circuit breaker - frame III 3200 to 4000 A

### Technical characteristics:

- Standards: IEC 60947-2
- Current rating: 3200A / 4000A
- Protection controller: microprocessor based LSI and LSiG
- Fixed and draw out version
- Breaking and short time withstand capacity (400 / 415V)  
Icu = 100kA  
Ics = 100% Icu  
Icw = 100kA (1s) / 57kA (3s)



HWP440B3






Designation	Rated current	Pole	Cat. ref. w/o earth fault 100kA	Cat. ref. with earth fault 100kA
<b>Draw out circuit breaker</b>	3200A	3	HWP332A3	HWP332B3
	4000A	3	HWP340A3	HWP340B3
	3200A	4	HWP432A3	HWP432B3
	4000A	4	HWP440A3	HWP440B3
<b>Fixed circuit breaker</b>	3200A	3	HWP332C3	HWP332D3
	4000A	3	HWP340C3	HWP340D3
	3200A	4	HWP432C3	HWP432D3
	4000A	4	HWP440C3	HWP440D3





**Accessories description**

Hager ACB offer comes with a complete range of accessories. Most of the accessories, especially the electrical ones, are common for all breakers.

The standard breaker is delivered with four auxiliaries contacts 4NO + 4NC.

	Designation	Technical information	Rated current (A)/ Voltage (V)	Pack qty	Cat. ref.
	<b>Additional electrical position indication</b>			1	<b>HWX113</b>
	<b>Closing release</b>	AC 50/60 Hz AC 50/60 Hz AC 50/60 Hz DC DC	110V 240V 415V 24/30V 48/60V	1 1 1 1 1	<b>HWX251</b> <b>HWX253</b> <b>HWX254</b> <b>HWX255</b> <b>HWX257</b>
	<b>Shunt release</b>	AC 50/60 Hz AC 50/60 Hz AC 50/60 Hz DC DC	110V 240V 415V 24/30V 48/60V	1 1 1 1 1	<b>HWX211</b> <b>HWX213</b> <b>HWX214</b> <b>HWX215</b> <b>HWX217</b>
	<b>Under voltage release (with delay)</b>	AC 50 Hz AC 50 Hz AC 50 Hz DC	110V 240V 415V 48V	1 1 1 1	<b>HWX241</b> <b>HWX243</b> <b>HWX244</b> <b>HWX247</b>
	<b>Under voltage release (without delay)</b>	AC 50 Hz AC 50 Hz AC 50 Hz DC DC	110V 240V 415V 24/30V 48V	1 1 1 1 1	<b>HWX231</b> <b>HWX233</b> <b>HWX234</b> <b>HWX235</b> <b>HWX237</b>
	<b>Electric charging device (motor)</b>	AC 50/60 Hz AC 50/60 Hz AC 50/60 Hz DC DC	110V 240V 415V 24/30V 48/60V	1 1 1 1 1	<b>HWX311</b> <b>HWX313</b> <b>HWX314</b> <b>HWX315</b> <b>HWX317</b>

	Designation	Technical information	Pack qty	Cat. ref.
	<b>Locking arrangement for OFF button</b>	castell lock	1	<b>HWY141</b>
		profalux lock	1	<b>HWY144</b>
	<b>Locking arrangement for all position</b>	castell lock	1	<b>HWY151</b>
		profalux lock	1	<b>HWY154</b>
	<b>Locking arrangement for isolated position</b>	castell lock	1	<b>HWY131</b>
		profalux lock	1	<b>HWY134</b>
	<b>Mechanical interlock (cable type)</b>	two incomers	1	<b>HWY121</b>
		three incomers	1	<b>HWY122</b>
		Two incomers and one standby	1	<b>HWY123</b>
		Two incomers and one bus coupler	1	<b>HWY124</b>
	<b>External neutral current transformer</b>	frame I 800A	1	<b>HWW213</b>
		frame I 1000A	1	<b>HWW214</b>
		frame I 1250A	1	<b>HWW215</b>
		frame I 1600A	1	<b>HWW216</b>
		frame I 2000A	1	<b>HWW217</b>
		frame II 800A	1	<b>HWW222</b>
		frame II 1000A	1	<b>HWW223</b>
		frame II 1250A	1	<b>HWW224</b>
		frame II 1600A	1	<b>HWW225</b>
		frame II 2000A	1	<b>HWW226</b>
		frame II 2500A	1	<b>HWW227</b>
		frame II 3200A	1	<b>HWW228</b>
		frame III 3200A	1	<b>HWW233</b>
		frame III 4000A	1	<b>HWW234</b>
	<b>Terminal adaptor</b>	for frame I and frame III, horizontal, vertical (2 per pole for frame I, 4 per pole for frame III.)	1	<b>HWY311</b>
		for frame II, (2 per pole) 800A to 2500A, horizontal and vertical	1	<b>HWY321</b>
		3200A, horizontal	1	<b>HWY324</b>
		3200A, vertical	1	<b>HWY325</b>
	<b>Door interlock</b>		1	<b>HWY112</b>
	<b>Operation counter</b>		1	<b>HWY211</b>

HWY144

HWY151

HWY154

HWY112

HWY211



**Design by Hager**  
In harmony with Hager enclosures and modular products.




**Visibility of auxiliaries fitted**  
Indicates type of auxiliary mounted in breaker.



**Electronic trip unit (LSI)**  
Is permitting total selectivity and generator protection.



**Integrated padlocking facility**  
Nice solution for maintenance.



**Breaking capacity**  
18 to 70kA, Icu 415V AC, covers all applications.



**Complete range of accessories**  
Rotary handles, padlocks, motors, terminal covers.



**Easy mounting of auxiliaries**  
Easy opening of secondary cover, clip-on type auxiliaries.



**Flexible connection**  
Collar terminals, front and rear connections, extended connections, spreaders ...

Frame			x160				x250			h250 TM	
Product			Switch	MCCB				Switch	MCCB		MCCB
Reference			HCA	HDA	HHA	HNA	HCB	HHB	HNB	HHG	
Number of poles			[No.]	3-4	1-2-3-4	1-2-3-4	3-4	3-4			3-4
Electrical characteristics											
Rated current	In	[A]	160				250			250	
Current rated range		[A]	125-160	16-125 (1P), 16-160 (2,3,4P)				250	100-250		20-250
Rated service voltage, (AC)	Ue	[V]	220-440				220-440			220-690	
Frequency	f	[Hz]	50/60				50/60			50/60	
Rated insulation voltage	Ui	[V]	690				800			800	
Rated impulse withstand voltage	Uimp	[kV]	8				8			8	
Rated ultimate short-circuit breaking capacity, (Icu)											
(AC) 50-60 Hz 220/230 V	Icu	[kA]	-	25	35	85	-	35	85	35	
(AC) 50-60 Hz 380/415 V	Icu	[kA]	-	18	25	40	-	25	40	25	
(AC) 50-60 Hz 480/500/525 V	Icu	[kA]	-	-	-	-	-	-	-	10	
(AC) 50-60 Hz 660/690 V	Icu	[kA]	-	-	-	-	-	-	-	-	
(DC) 250 V - 2 poles in series	Icu	[kA]	-	10	10	10	-	9	9	25	
Rated service short-circuit breaking capacity, (Ics)											
(AC) 50-60 Hz 220/230 V	Ics	[kA]	-	25	25	40	-	25	40	27	
(AC) 50-60 Hz 380/415 V	Ics	[kA]	-	18	20	20	-	20	20	19	
(AC) 50-60 Hz 480/500/525 V	Ics	[kA]	-							7,5	
(AC) 50-60 Hz 660/690 V	Ics	[kA]	-	-			-			-	
(DC) 250 V - 2 poles in series	Ics	[kA]	-	5	5	5	-	5	5	19	
Rated short-circuit making capacity	Icm	[kA]	2,8	-	-	-	9	-	-	-	
Rated short-time withstand current for 1s	Icw	[kA]	2	-	-	-	3,6	-	-	-	
Category of utilisation (EN 60947-2)			-	A			-	A		A	
Calibration temperature			-	50°C			-	50°C		50°C	
Derating	40°C		-	100%			-	100%		100%	
	50°C		-	100%			-	100%		100%	
	55°C		-	95%			-	94%		94%	
	60°C		-	93%			-	91%		91%	
	65°C		-	90%			-	88%		88%	
Suitability for isolation			ok				ok			ok	
Electric endurance in number of cycles			10000				10000			10000	
Mechanical endurance in number of operations			20000				20000			30000	
Operating temperature			-25 to +70°C				-5 to +70°C			-25 to +70°C	
Storage temperature			-35 to +70°C				-35 to +70°C			-35 to +70°C	
Power loss (at In for 3P)		[W]	39				60			65	
Reference standard			IEC 60947-3		IEC 60947-2		IEC 60947-3		IEC 60947-2		IEC 60947-2
Releases: switch			ok		-		ok		-		-
Releases: TM (thermomagnetic)			-	ok				-	ok		ok
T fixed, M fixed			-	ok				-	ok		-
T adjustable, M fixed			-	ok				-	-		-
T adjustable, M adjustable			-	-				-	ok		ok
Thermal adjustment value			-	0,63 to 1 x In				-	0,63 to 1 x In		0,63 to 1 x In
Magnetic adjustment value			-	-				-	6-8-10-13 x In (200A) 5-7-9-11 In (250A)		6-8-10-13 x In
Releases: LSI (electronic)			-	-				-	-		-
Long delay			-	-				-	-		-
Short delay			-	-				-	-		-
Time delay			-	-				-	-		-
Accessories											
Auxiliary switches			#1				#1			#2	
Alarm switches			#1				#1			#2	
Shunt release			#1				#1			#2	
Undervoltage release			#1				#1			#2	
Rotary handle mechanism			ok				ok			ok	
Motor operator			-				ok			ok	
Padlockable handle			integrated				integrated			ok	
Interphase barriers			ok				integrated			integrated	
Din rail adapter			ok				-			-	
Terminations											
Standard terminal type			cage				lugs			lugs	
Maximum terminal capacity			95 mm²				185 mm² (cage)			185 mm² (cage)	
Terminal width		mm	-				25			25	
Terminal shields			ok				ok			ok	
Cage terminal			integrated				ok			ok	
Extended connections			ok				ok			ok	
Rear connections			no				ok			ok	
Dimensions											
Height		mm	130				165			165	
Width	1P	mm	-	25		-	-			-	
	2P	mm	-	50		-	-			-	
	3P	mm	75				105			105	
	4P	mm	100				140			140	
Depth		mm	68				68			68	
Weight	1P	kg	-	0,29		-	-			-	
	2P	kg	-	0,48		-	-			-	
	3P	kg	0,715				1,3			1,5	
	4P	kg	0,95				1,6			1,9	

h400			h630			h1000			h1600					
MCCB			Switch			MCCB			Switch			MCCB		
	HNG	HEG	HHD	HND	HCD	HND	HED	HCE	HNE / HNK	HEE / HEK	HCF	HNF	HEF	
			3-4		3-4			3-4			3-4			
			400		630			1000			1600			
			250-400		400-630	250-630		630-800-1000			1250-1600			
			220-690		220-690			220-690			220-690			
			50/60		50/60			50/60			50/60			
			800		800			800			800			
			8		8			8			8			
			35	85	-	85	100	-	85 (800A) 75 (1000A)	100	-	100	100	
			50	65	-	50	70	-	50	70	-	50	70	
			25	25	-	30	30	-	30	30	-	45	65	
			7,5	7,5	-	20	20	-	20	20	-	25	45	
			40	40	-			-	-	-	-	-	-	
			65	85	-	85	85	-	85 (800A) 75 (1000A)	100 (800A) 75 (1000A)	-	75	75	
			25	36	-	50	50	-	50	50	-	50	50	
			25	25	-	30	30	-	30	30	-	45	50	
			7,5	7,5	-	15	15	-	20	20	-	25	34	
			40	40	-			-	-	-	-	-	-	
			-	-	9	-	-	20	-	-	45	-	-	
			-	-	5 (0,3s)	-	-	10KA (0,3s)	-	-	20 (0,3s)	-	-	
			A		-	B (400A) - A (630A)		-	B (800A) - A (1000A)		-	B		
			50°C		-	50°C		-	50°C		-	50°C		
			100%		-	100%		-	100%		-	100%		
			100%		-	100%		-	100%		-	100%		
			95%		-	95%		-	95%		-	95%		
			92%		-	90%		-	90%		-	90%		
			89%		-	80%		-	80%		-	80%		
			ok		ok			ok			ok			
			4500		4500			4500			4500			
			15000		15000			15000			15000			
			-25 to +70°C		-25 to +70°C			-25 to +70°C			-25 to +70°C			
			-35 to +70°C		-35 to +70°C			-35 to +70°C			-35 to +70°C			
			75		150			150			170			
			IEC 60947-2		IEC 60947-3	IEC 60947-2		IEC 60947-3	IEC 60947-2		IEC 60947-3	IEC 60947-2		
			-		ok	-		ok	-		ok	-		
			ok		-			-			-			
			-		-			-			-			
			-		-			-			-			
			ok		-			-			-			
			0,63 to 1 x In		-			-			-			
			6-8-10-12 x In		-			-			-			
			-		-	ok		-	ok		-	ok		
			-		-	0,4 to 1 x Ir		-	0,4 to 1 x Ir		-	0,4 to 1 x In		
			-		-	2,5 to 10 x Ir (400A) 2,5 to 8 x Ir (630A)		-	2,5 to 10 x Ir (800A) 2,5 to 8 x Ir (1000A)		-	2,5 to 10 x Ir		
			-		-	0,1 - 0,2s		-	0,1 - 0,2s		-	0,1 - 0,2s		
			#2		#2			#2			#2			
			#2		#2			#2			#2			
			#2		#2			#2			#2			
			#2		#2			#3			#3			
			ok		ok			ok			ok			
			ok		ok			ok			ok			
			ok		ok			ok			ok			
			integrated		integrated			integrated			integrated			
			-		-			-			-			
			lugs		lugs			lugs			lugs			
			240 mm² (cage)		-			-			-			
			30		30			45			45			
			ok		ok			ok			ok			
			ok		-			-			-			
			ok		integrated			integrated			integrated			
			ok		ok			ok			ok			
			260		260			273/433			370/570			
			-		-			-			-			
			-		-			-			-			
			140		140			210			210			
			185		185			280			280			
			97		97			99,5			140			
			-		-			-			-			
			-		-			-			-			
			4,2		4,3			11			27			
			5.6		5.7			14.8						

**Moulded case circuit breakers x160**

Mechanical test button, lockable settings,  
integrated padlocking handle  
Ø 4mm.

**Connection capacity**

95□ rigid cables  
70□ flexible cables  
Complies with IEC 60947-2

**Switch disconnectors**

allows tripping using a shunt trip unit (optional)  
Complies with IEC 60947-3  
AC 22/23A



HDA 125Z

Designation	In	Cat. ref.			
		1P	2P	3P	4P
<b>MCCBs x160 18kA</b>	16A	HDA 014Z	HDA 015Z	HDA 016Z	HDA 017Z
<b>TM</b>	20A	HDA 018Z	HDA 019Z	HDA 020Z	HDA 021Z
breaking capacity	25A	HDA 023Z	HDA 024Z	HDA 025Z	HDA 026Z
Ics : 18 kA	32A	HDA 030Z	HDA 031Z	HDA 032Z	HDA 033Z
(400/415 V AC)	40A	HDA 038Z	HDA 039Z	HDA 040Z	HDA 041Z
	50A	HDA 048Z	HDA 049Z	HDA 050Z	HDA 051Z
fixed thermal	63A	HDA 061Z	HDA 062Z	HDA 063Z	HDA 064Z
1x In	80A	HDA 078Z	HDA 079Z	HDA 080Z	HDA 081Z
fixed magnetic	100A	HDA 098Z	HDA 099Z	HDA 100Z	HDA 101Z
> 10 x In	125A	HDA 123Z	HDA 124Z	HDA 125Z	HDA 126Z
	160A	-	HDA 159Z	HDA 160Z	HDA 161Z
	*125A	HDA 123P	HDA 124P	HDA 125P	HDA 126P
	*160A	-	HDA 159P	HDA 160P	HDA 161P
adjustable thermal	25A	-	-	HDA 025U	HDA 026U
0,63 - 0,8 - 1 x In	40A	-	-	HDA 040U	HDA 041U
fixed magnetic	63A	-	-	HDA 063U	HDA 064U
> 10 x In	80A	-	-	HDA 080U	HDA 081U
	100A	-	-	HDA 100U	HDA 101U
	125A	-	-	HDA 125U	HDA 126U
	160A	-	-	HDA 160U	HDA 161U
	*125A	-	-	HDA 125S	HDA 126S
	*160A	-	-	HDA 160S	HDA 161S



HDA 126U

<b>MCCBs x160 25kA</b>	16A	HHA 014Z	HHA 015Z	HHA 016Z	HHA 017Z
<b>TM</b>	20A	HHA 018Z	HHA 019Z	HHA 020Z	HHA 021Z
breaking capacity	25A	HHA 023Z	HHA 024Z	HHA 025Z	HHA 026Z
Ics : 20 kA	32A	HHA 030Z	HHA 031Z	HHA 032Z	HHA 033Z
(400/415 V AC)	40A	HHA 038Z	HHA 039Z	HHA 040Z	HHA 041Z
	50A	HHA 048Z	HHA 049Z	HHA 050Z	HHA 051Z
fixed thermal	63A	HHA 061Z	HHA 062Z	HHA 063Z	HHA 064Z
1x In	80A	HHA 078Z	HHA 079Z	HHA 080Z	HHA 081Z
fixed magnetic	100A	HHA 098Z	HHA 099Z	HHA 100Z	HHA 101Z
> 10 x In	125A	HHA 123Z	HHA 124Z	HHA 125Z	HHA 126Z
	160A	-	HHA 159Z	HHA 160Z	HHA 161Z
	*125A	HHA 123P	HHA 124P	HHA 125P	HHA 126P
	*160A	-	HHA 159P	HHA 160P	HHA 161P
adjustable thermal	25A	-	-	HHA 025U	-
0,63 - 0,8 - 1 x In	40A	-	-	HHA 040U	-
fixed magnetic	63A	-	-	HHA 063U	-
> 10 x In	80A	-	-	HHA 080U	-
	100A	-	-	HHA 100U	-
	125A	-	-	HHA 125U	-
	160A	-	-	HHA 160U	-
	*125A	-	-	HHA 125S	-
	*160A	-	-	HHA 160S	-

Note : \*The references are without collar terminal



HNA 160Z

Designation	In	Cat. ref.			
		1P	2P	3P	4P
<b>MCCBs x160 40kA</b>	16A	-	-	<b>HNA 016Z</b>	<b>HNA 017Z</b>
<b>TM</b>	20A	-	-	<b>HNA 020Z</b>	<b>HNA 021Z</b>
breaking capacity	25A	-	-	<b>HNA 025Z</b>	<b>HNA 026Z</b>
Ics : 20 kA	32A	-	-	<b>HNA 032Z</b>	<b>HNA 033Z</b>
(400/415 V AC)	40A	-	-	<b>HNA 040Z</b>	<b>HNA 041Z</b>
	50A	-	-	<b>HNA 050Z</b>	<b>HNA 051Z</b>
fixed thermal	63A	-	-	<b>HNA 063Z</b>	<b>HNA 064Z</b>
1 x In	80A	-	-	<b>HNA 080Z</b>	<b>HNA 081Z</b>
fixed magnetic	100A	-	-	<b>HNA 100Z</b>	<b>HNA 101Z</b>
> 10 x In	125A	-	-	<b>HNA 125Z</b>	<b>HNA 126Z</b>
	160A	-	-	<b>HNA 160Z</b>	<b>HNA 161Z</b>
	*125A	-	-	<b>HNA 125P</b>	<b>HNA 126P</b>
	*160A	-	-	<b>HNA 160P</b>	<b>HNA 161P</b>
adjustable thermal	25A	-	-	<b>HNA 025U</b>	-
0,63 - 0,8 - 1 x In	40A	-	-	<b>HNA 040U</b>	-
fixed magnetic	63A	-	-	<b>HNA 063U</b>	-
> 10 x In	80A	-	-	<b>HNA 080U</b>	-
	100A	-	-	<b>HNA 100U</b>	-
	125A	-	-	<b>HNA 125U</b>	-
	160A	-	-	<b>HNA 160U</b>	-
	*125A	-	-	<b>HNA 125S</b>	<b>HNA 126S</b>
	*160A	-	-	<b>HNA 160S</b>	<b>HNA 161S</b>



HJA 063Z

<b>MCCBs x160 25kA</b>	16A	-	-	<b>HJA 016Z</b>	<b>HJA 017Z</b>
<b>TM</b>	20A	-	-	<b>HJA 020Z</b>	<b>HJA 021Z</b>
breaking capacity	25A	-	-	<b>HJA 025Z</b>	<b>HJA 026Z</b>
Ics : 25 kA	32A	-	-	<b>HJA 032Z</b>	<b>HJA 033Z</b>
(400/415 V AC)	40A	-	-	<b>HJA 040Z</b>	<b>HJA 041Z</b>
	50A	-	-	<b>HJA 050Z</b>	<b>HJA 051Z</b>
fixed thermal	63A	-	-	<b>HJA 063Z</b>	<b>HJA 064Z</b>
1 x In	80A	-	-	<b>HJA 080Z</b>	<b>HJA 081Z</b>
fixed magnetic	100A	-	-	<b>HJA 100Z</b>	<b>HJA 101Z</b>
> 10 x In	125A	-	-	<b>HJA 125Z</b>	<b>HJA 126Z</b>
	160A	-	-	<b>HJA 160Z</b>	<b>HJA 161Z</b>

<b>Switch disconnectors x160</b>	125A	-	-	<b>HCA 125Z</b>	<b>HCA 126Z</b>
suitable for	160A	-	-	<b>HCA 160Z</b>	<b>HCA 161Z</b>
AC22A / AC 23A					

Ue: 415 V AC

Icw (1s): 2 kA

Note: \* The references are without collar terminal



<b>Technical characteristics</b> Mechanical test button, lockable settings, integrated padlocking handle Ø 4mm.  Complies with IEC 60947-2	<b>Connection:</b> directly on copper cable terminal, with end lug max. width: 25 mm Connection capacity: 185 <sup>□</sup> rigid cables Complies with IEC 60947-2	<b>Switch disconnectors</b> allows tripping using a shunt trip unit (optional) Complies with IEC 60947-3 AC 22/23A
--	---	--



HNB 250Z



HNB 100U

Designation	Characteristics	In	Cat. ref.	
			3P	4P
<b>MCCBs x250 25kA</b> <b>TM</b> breaking capacity Icu : 25 kA (400/415 V AC) Ics: 20kA	fixed thermal: 1 x In fixed magnetic: ≥10 x In	100A	<b>HHB 100Z</b>	<b>HHB 101Z</b>
		125A	<b>HHB 125Z</b>	<b>HHB 126Z</b>
		160A	<b>HHB 160Z</b>	<b>HHB 161Z</b>
		200A	<b>HHB 200Z</b>	<b>HHB 201Z</b>
		250A	<b>HHB 250Z</b>	<b>HHB 251Z</b>
	adjustable thermal: 0,63 - 0,8 - 1x In adjustable magnetic: 6 - 8 - 10 - 13 x In (100 - 200A) 5 - 7 - 9 - 11 x In (250A) 3P, 3 trip units - 4P - neutral setting: 0 or 100%	100A	<b>HHB 100U</b>	<b>HHB 101U</b>
		125A	<b>HHB 125U</b>	<b>HHB 126U</b>
		160A	<b>HHB 160U</b>	<b>HHB 161U</b>
		200A	<b>HHB 200U</b>	<b>HHB 201U</b>
		250A	<b>HHB 250U</b>	<b>HHB 251U</b>
<b>MCCBs x250 40kA</b> <b>TM</b> breaking capacity Icu : 40 kA (400/415 V AC) Ics: 20 kA	fixed thermal: 1 x In fixed magnetic: ≥10 x In	100A	<b>HNB 100Z</b>	<b>HNB 101Z</b>
		125A	<b>HNB 125Z</b>	<b>HNB 126Z</b>
		160A	<b>HNB 160Z</b>	<b>HNB 161Z</b>
		200A	<b>HNB 200Z</b>	<b>HNB 201Z</b>
		250A	<b>HNB 250Z</b>	<b>HNB 251Z</b>
	adjustable thermal: 0,63 - 0,8 - 1x In adjustable magnetic: 6 - 8 - 10 - 13 x In (100 - 200A) 5 - 7 - 9 - 11 x In (250A) 3P, 3 trip units - 4P - neutral setting: 0 or 100%	100A	<b>HNB 100U</b>	<b>HNB 101U</b>
		125A	<b>HNB 125U</b>	<b>HNB 126U</b>
		160A	<b>HNB 160U</b>	<b>HNB 161U</b>
		200A	<b>HNB 200U</b>	<b>HNB 201U</b>
		250A	<b>HNB 250U</b>	<b>HNB 251U</b>
<b>Switch disconnectors x250</b>	capacity suitable for AC 22/23A	250A	<b>HCB 250Z</b>	<b>HCB 251Z</b>



**Moulded case circuit breakers h250**
**Thermal magnetic trip unit:**

 thermal adjustment: 0.63 to 1  $I_n$ 

magnetic adjustment:

 6-8-10-13 x  $I_n$ 

3P &amp; 4P (3P only for 25kA)

Mechanical test button,

lockable settings,

Connection:

Directly on copper cable

terminal,

with end lug max. width: 25 mm

Comply with IEC 60 947-2.



HHG250U

Designation	Characteristics	$I_n$	Cat. ref.	
			3P	4P
<b>MCCBs h250 25kA TM</b>	breaking capacity	20A	<b>HHG020U</b>	-
	$I_{cu}$ : 25 kA (400/415 V AC)	32A	<b>HHG032U</b>	-
	$I_{cs}$ : 19 kA	50A	<b>HHG050U</b>	-
		63A	<b>HHG063U</b>	-
	adjustable thermal	100A	<b>HHG100U</b>	-
	0.63 to 1 x $I_n$	125A	<b>HHG125U</b>	-
	adjustable magnetic	160A	<b>HHG160U</b>	-
	6 - 8 - 10 - 13 x $I_n$	200A	<b>HHG200U</b>	-
		250A	<b>HHG250U</b>	-

<b>MCCBs h250 50kA TM</b>	breaking capacity	20A	<b>HNG020U</b>	<b>HNG021U</b>
	$I_{cu}$ : 30 kA (20-32A)	32A	<b>HNG032U</b>	<b>HNG033U</b>
	$I_{cu}$ : 50 kA	63A	<b>HNG063U</b>	<b>HNG064U</b>
	(400/415 V AC)	100A	<b>HNG100U</b>	<b>HNG101U</b>
	$I_{cs}$ : 25 kA	125A	<b>HNG125U</b>	<b>HNG126U</b>
		160A	<b>HNG160U</b>	<b>HNG161U</b>
	adjustable thermal	200A	<b>HNG200U</b>	<b>HNG201U</b>
	0.63 to 1 x $I_n$	250A	<b>HNG250U</b>	<b>HNG251U</b>
	adjustable magnetic			
	6 - 8 - 10 - 13 x $I_n$			

<b>MCCBs h250 65kA TM</b>	breaking capacity	50A	<b>HEG050U</b>	<b>HEG051U</b>
	$I_{cu}$ : 65 kA (400/415 V AC)	63A	<b>HEG063U</b>	<b>HEG064U</b>
	$I_{cs}$ : 36 kA	100A	<b>HEG100U</b>	<b>HEG101U</b>
		125A	<b>HEG125U</b>	<b>HEG126U</b>
	adjustable thermal	160A	<b>HEG160U</b>	<b>HEG161U</b>
	0.63 to 1 x $I_n$	200A	<b>HEG200U</b>	<b>HEG201U</b>
	adjustable magnetic	250A	<b>HEG250U</b>	<b>HEG251U</b>
	6 - 8 - 10 - 13 x $I_n$			



HNH250U

<b>MCCBs h250 50kA TM+</b>	breaking capacity	20A	<b>HNH020U</b>	<b>HNH021U</b>
	$I_{cu}$ : 50 kA (400/415 V AC)	32A	<b>HNH032U</b>	<b>HNH033U</b>
	$I_{cs}$ : 50 kA	50A	<b>HNH050U</b>	<b>HNH051U</b>
		63A	<b>HNH063U</b>	<b>HNH064U</b>
	adjustable thermal	100A	<b>HNH100U</b>	<b>HNH101U</b>
	0.63 to 1 x $I_n$	125A	<b>HNH125U</b>	<b>HNH126U</b>
	adjustable magnetic	160A	<b>HNH160U</b>	<b>HNH161U</b>
	6 - 8 - 10 - 13 x $I_n$	250A	<b>HNH250U</b>	<b>HNH251U</b>

<b>MCCBs h250 70kA TM+</b>	breaking capacity	20A	<b>HEH020U</b>	<b>HEH021U</b>
	$I_{cu}$ : 70 kA (400/415 V AC)	32A	<b>HEH032U</b>	<b>HEH033U</b>
	$I_{cs}$ : 50 kA	50A	<b>HEH050U</b>	<b>HEH051U</b>
		63A	<b>HEH063U</b>	<b>HEH064U</b>
	adjustable thermal	100A	<b>HEH100U</b>	<b>HEH101U</b>
	0.63 to 1 x $I_n$	125A	<b>HEH125U</b>	<b>HEH126U</b>
	adjustable magnetic	160A	<b>HEH160U</b>	<b>HEH161U</b>
	6 - 8 - 10 - 13 x $I_n$	250A	<b>HEH250U</b>	<b>HEH251U</b>

<b>Technical characteristics</b> Mechanical test button, lockable settings	<b>Connection:</b> directly on copper cable terminal, with end lug max. width: 30 mm Complies with IEC 60947-2)	<b>Switch disconnectors</b> allows tripping using a shunt trip unit (optional)  Complies with IEC 60947-3 AC 23A / DC 22A
--	---	--



HHD 400U



HND 631U

Designation	Characteristics	In	Cat. ref.	
			3P	4P
<b>MCCBs h400 25kA TM</b>  breaking capacity Icu : 25 kA (400/415 V AC) Ics: 25 kA	adjustable thermal: 0.63 to 1 x In adjustable magnetic: 6 to 12 x In	250A 400A	<b>HHD 250U</b> <b>HHD 400U</b>	- -
<b>MCCBs h400 50kA TM</b>  breaking capacity Icu : 50 kA (400/415 V AC) Ics: 50 kA	adjustable thermal: 0.63 to 1 x In adjustable magnetic: 6 to 12 x In	250A 400A	<b>HND 250U</b> <b>HND 400U</b>	<b>HND 251U</b> <b>HND 401U</b>
<b>MCCBs h630 50kA LSI</b>  breaking capacity Icu : 50 kA (400/415 V AC) Ics: 50 kA	adjustable thermal: Ir = 0.4 to 1 x In adjustable magnetic: 2.5 to 8 x Ir time delay: 0,1 - 0,2 s	400A 630A	<b>HND 400H</b> <b>HND 630U</b>	<b>HND 401H</b> <b>HND 631U</b>
<b>MCCBs h630 70kA LSI</b>  breaking capacity Icu : 70 kA (400/415 V AC) Ics: 50 kA	adjustable thermal: Ir = 0.4 to 1 x In adjustable magnetic: 2.5 to 10 x Ir (400A) 2.5 to 8 x Ir (630A) time delay: 0,1 - 0,2 s	400A 630A	<b>HED 400U</b> <b>HED 630U</b>	<b>HED 401U</b> <b>HED 631U</b>
<b>Switch disconnectors</b>	suitable for AC 22A / AC 23A	400A 630A	<b>HCD 400U</b> <b>HCD 630U</b>	<b>HCD 401U</b> <b>HCD 631U</b>

**Moulded case circuit breakers h800****Thermal magnetic trip unit TM:**

- thermal adjustment: from 0.63 to 1 x I<sub>n</sub>
- magnetic adjustment: from 6 to 12 x I<sub>n</sub>

**Connection:**

Directly on copper cable terminal,  
with end lug max. width: 30 mm

Comply with IEC 60 947-2.

**Moulded case circuit breakers h1000****Electronic trip unit LSI:**

- long delay (thermal equivalent) adjustable:  
I<sub>r</sub> = 0,4 to 1 x I<sub>n</sub>
- short delay (magnetic equivalent) adjustable:  
2,5 to 10 x I<sub>r</sub> (630-800A)  
and 2,5 to 8 x I<sub>r</sub> (1000A)
- time delay: 0,1-0,2 s

3P & 4P (adjustable neutral 0 - 50% - 100%).  
Mechanical test button,

lockable settings.

**Connection:**

Directly on copper cable terminal,  
with end lug max. width: 50 mm

Comply with IEC 60 947-2.



Switch Disconnectors

Comply with IEC 60 947-3.  
AC 23A / DC 22A



HNE970U

Designation	Characteristics	In	Cat. ref.	
			3P	4P
<b>MCCBs h800 50kA TM</b>	breaking capacity	630A	<b>HNK630U</b>	<b>HNK631U</b>
	I <sub>cu</sub> : 50 kA (400/415 V AC) I <sub>cs</sub> : 50 kA	800A	<b>HNK800U</b>	<b>HNK801U</b>
	adjustable thermal 0.63 to 1 x I <sub>n</sub> adjustable magnetic 6 to 12 x I <sub>n</sub>			
<b>MCCBs h800 70kA TM</b>	breaking capacity	630A	<b>HEK630U</b>	<b>HEK631U</b>
	I <sub>cu</sub> : 70 kA (400/415 V AC) I <sub>cs</sub> : 50 kA	800A	<b>HEK800U</b>	<b>HEK801U</b>
	adjustable thermal 0.63 to 1 x I <sub>n</sub> adjustable magnetic 6 to 12 x I <sub>n</sub>			
<b>MCCBs h1000 50kA LSI</b>	breaking capacity	800A	<b>HNE800U</b>	<b>HNE801U</b>
	I <sub>cu</sub> : 50 kA (400/415 V AC) I <sub>cs</sub> : 50 kA	1000A	<b>HNE970U</b>	<b>HNE971U</b>
	adjustable thermal I <sub>r</sub> = 0,4 to 1 x I <sub>n</sub> adjustable magnetic 2,5 to 10 x I <sub>r</sub> (630 - 800A) 2,5 to 8 x I <sub>r</sub> (1000A) time delay: 0,1-0,2 s			
	neutral setting from 0-50 to 100%			
	* without straight extended connection			
<b>MCCBs h1000 70kA LSI</b>	breaking capacity	800A	<b>HEE800U</b>	<b>HEE801U</b>
	I <sub>cu</sub> : 70 kA (400/415 V AC) I <sub>cs</sub> : 50 kA	1000A	<b>HEE970U</b>	<b>HEE971U</b>
	adjustable thermal I <sub>r</sub> = 0,4 to 1 x I <sub>n</sub> adjustable magnetic 2,5 to 10 x I <sub>r</sub> (800A) 2,5 to 8 x I <sub>r</sub> (1000A) time delay: 0,1-0,2 s			
	neutral setting from 0-50 to 100%			
<b>Switch disconnectors</b>	suitable for AC 22A / AC 23A U <sub>e</sub> : 415 V AC	800A	<b>HCE800U</b>	<b>HCE801U</b>
	I <sub>cw</sub> (0,3 s) = 10 kA	1000A	<b>HCE970U</b>	<b>HCE971U</b>

 HNF 990U	<b>Technical characteristics</b> Mechanical test button, lockable settings.	<b>Connection:</b> directly on copper cable terminal, with end lug max. width: 60 mm  Complies with IEC 60947-2	<b>Switch disconnectors</b> allows tripping using a shunt trip unit (optional)  Complies with IEC 60947-3 AC 23A / DC 22A	
	<i>Designation</i>	<i>Characteristics</i>	<i>In</i>	<i>Cat. ref.</i>
				<i>3P</i> <i>4P</i>
 HNF 990U	<b>MCCBs h1600 50kA</b> <b>LSI</b>  breaking capacity Icu : 50 kA (400/415 V AC) Ics: 50 kA	adjustable thermal: Ir = 0,4 to 1 x In adjustable magnetic: 2,5 to 10 x Ir time delay: 0,1-0,2 s  neutral setting 0, 50, 100%	1250A 1600A	<b>HNF 980U</b> <b>HNF 981U</b> <b>HNF 990U</b> <b>HNF 991U</b>
	<b>MCCBs h1600 70kA</b> <b>LSI</b>  breaking capacity Icu : 70 kA (400/415 V AC) Ics: 50 kA	adjustable thermal Ir = 0,4 to 1 x In adjustable magnetic 2,5 to 10 x Ir time delay: 0,1-0,2 s  neutral setting from 0, 50, 100%	1250A 1600A	<b>HEF 980U</b> <b>HEF 981U</b> <b>HEF 990U</b> <b>HEF 991U</b>
	<b>Switch disconnectors</b>	suitable for AC 22A / AC 23A	1250A 1600A	<b>HCF 980U</b> <b>HCF 981U</b> <b>HCF 990U</b> <b>HCF 991U</b>



HXA004H



HXA014H



HXA021H



HXA030H



HXA039HME



HXD042H



HXC004H



HXC014H



HXA024H



HXD030H



HXC039H



HXD039H

Designation	Frame	In/a Ue/V	3P Cat. ref.	4P Cat. ref.
Shunt trip release	x160, x250	24V DC	HXA001H	HXA001H
		48V DC	HXA002H	HXA002H
		110V AC	HXA003H	HXA003H
		230V AC	HXA004H	HXA004H
		400V AC	HXA005H	HXA005H
	h250, h400-h630, h1000, h1600	24V DC	HXC001H	HXC001H
		48V DC	HXC002H	HXC002H
		110V AC	HXC003H	HXC003H
		230V AC	HXC004H	HXC004H
		400V AC	HXC005H	HXC005H
Undervoltage release	x160, x250	24V DC	HXA011H	HXA011H
		110V AC	HXA013H	HXA013H
		230V AC	HXA014H	HXA014H
		400V AC	HXA015H	HXA015H
		24V DC	HXC011H	HXC011H
	h250, h400-h630	110V AC	HXC013H	HXC013H
		230V AC	HXC014H	HXC014H
		400V AC	HXC015H	HXC015H
		24V DC	HXE011H	HXE011H
		110V AC	HXE013H	HXE013H
	h1000, h1600	230V AC	HXE014H	HXE014H
		400V AC	HXE015H	HXE015H
Auxiliary contact	x160, x250	1NO+1NC	HXA021H	HXA021H
	h250, h400-h630, h1000, h1600	1NO+1NC	HXC021H	HXC021H
Alarm contact	x160, x250	1NO+1NC	HXA024H	HXA024H
	h250, h400-h630, h1000, h1600	1NO+1NC	HXC024H	HXC024H
Direct rotary handle	x160		HXA030H	HXA030H
	x250		HXB030H	HXB030H
	h250		HXC030H	HXC030H
	h400-h630		HXD030H	HXD030H
	h1000		HXE030H	HXE030H
	h1600		HXF030H	HXF030H
Extended rotary handle	x160		HXA031H	HXA031H
	x250		HXB031H	HXB031H
	h250		HXC031H	HXC031H
	h400-h630		HXD031H	HXD031H
	h1000		HXE031H	HXE031H
	h1600		HXF031H	HXF031H
Padlock	x160, x 250 utility approved		HXA039HME	HXA039HME
	x160, x250		HXA039H	HXA039H
	h250		HXC039H	HXC039H
	h400-h630, h1000		HXD039H	HXD039H
	h1600		HXF039H	HXF039H
Motor operator	x250	24V DC	HXB040H	HXB040H
		220V AC	HXB042H	HXB042H
	h250	24V DC	HXC040H	HXC040H
		220V AC	HXC042H	HXC042H
	h400-h630	24V DC	HXD040H	HXD040H
		220V AC	HXD042H	HXD042H
	h1000	24V DC	HXE040H	HXE040H
		220V AC	HXE042H	HXE042H
	h1600	24V DC	HXF040H	HXF040H
		220V AC	HXF042H	HXF042H
Electrical inter lock for motor operator	x250/h250		HXB068H	HXB068H
	h400/h639/h1020		HXD068H	HXD068H
	x250/h250-h400/h630/h1000		HXB069H	HXB069H



Load break switches 20 to 160A



HAB406

Designation	Characteristics	In/A	Width in 17.5mm		Cat. ref.	
			3P	4P	3P	4P
Load break switches visible breaking	disconnecter modular design IP20 AC23	20A	2,5	3,5	HAB302	HAB402
		32A	2,5	3,5	HAB303	HAB403
		40A	2,5	3,5	HAB304	HAB404
		63A	2,5	3,5	HAB306	HAB406
		63A	3	4	HAC306	HAC406
		80A	3	4	HAC308	HAC408
		100A	3	4	HAC310	HAC410
		100A	4,5	6	HAD310	HAD410
		125A	4,5	6	HAD312	HAD412

Auxiliaries contacts In = 10A	1O + 1F	0,5	0,5	HZC311	HZC311
	2F	0,5	0,5	HZC312	HZC312

External handle IP55 locked with 3 padlocks	for LBS 20 to 100A	HZC010	HZC010
	for LBS 100 to 125A	HZC011	HZC011
	for LBS 100 to 125A	HZC014	HZC014



HZC014


Shaft extension	20 to 100A, 150mm	HZC111	HZC111
	20 to 100A, 200mm	HZC112	HZC112
	20 to 100A, 320mm	HZC113	HZC113
	100 to 125A, 150mm	HZC114	HZC114
	100 to 125A, 200mm	HZC115	HZC115
	100 to 125A, 320mm	HZC116	HZC116

Terminal shrouds top and bottom 2 pieces / packaging	20 to 63A	HZC211	HZC212
	63 to 100A	HZC213	HZC214
	100 to 125A	HZC215	HZC216

Load break switches  
160A, 200A, 250A for use as distribution board incomer



JK160S




JK200S

Designation	In/A	Cat. ref. 3P
Load break switches AC22/AC23	160A	JK160S
	200A	JK200S
	250A	JK250S





HA358





HZC101

Designation	Characteristics	In/A	Cat. ref. 3P	4P
Load break switches with handle	direct rotary handle AC22 and AC23	125A	HA351	HA451
		160A	HA352	HA452
		200A	HA353M	HA453M
		250A	HA354	HA454
		315A	HA355M	HA455M
		400A	HA357	HA457
		630A	HA358	HA458
		800A	HA360	HA460
		1250A	HA362	HA462
Auxiliaries contacts			HZ023	HZ023
Rotary handle	for extended shaft - 125 to 630A - 800 to 1250A - double hand		HZC002	HZC002
			HZC003	HZC003
			HZA001	HZA001
Shaft extension	125 to 630A, 200mm 125 to 630A, 320mm 800 to 1250A, 200mm 800 to 1250A, 320mm		HZC101	HZC101
			HZC102	HZC102
			HZC105	HZC105
			HZC106	HZC106



Technical Characteristics

Standards: IEC 60947-4-1  
DIN rail / Screw mounted aprevention  
Utilisation catageory: AC3  
Rated current at 380V / 400V AC  
High grade of coil insulation-class F

	Rated operational current I <sub>c</sub>	Kw	in-built AUX contact	Cat.ref.
 EW020_K	9A	4	1 NO	EW009_■
	12A	5.5	1 NO	EW012_■
	16A	7.5	1 NO	EW016_■
	22A	11	1 NO + 1 NC	EW020_■
	26A	11	1 NO + 1 NC	EW025_■
	32A	15	1 NO + 1 NC	EW032_■
	40A	20	1 NO + 1 NC	EW040_■
 EW040_J	55A	25	2 NO + 2 NC	EW050_■
	64A	30	2 NO + 2 NC	EW063_■
	72A	37	2 NO + 2 NC	EW070_■
	105A	55	2 NO + 2 NC	EW100_■
	115A	60	2 NO + 2 NC	EW120_■
	147A	80	2 NO + 2 NC	EW150_■
	179A	95	2 NO + 2 NC	EW180_■
	225A	120	2 NO + 2 NC	EW220_■
	300A	160	2 NO + 2 NC	EW300_■

EW040\_J





EW063\_M

Note: Replace ■ with coil voltages





- Coil voltages:
- C: 220V AC 50/60 Hz (EW009\_C ~ EW300\_C)
  - D: 380V AC 50/60 Hz (EW009\_D ~ EW300\_D)
  - H: 110V AC 50/60 Hz (EW009\_H ~ EW070\_H)
  - J: 230V AC 50Hz (EW009\_J ~ EW300\_J)
  - K: 240V AC 50Hz (EW009\_K ~ EW300\_K)
  - L: 400V AC 50Hz (EW009\_L ~ EW070\_L)
  - M: 415V AC 50Hz (EW009\_M ~ EW070\_M)


Technical Characteristics

3pole, 1NO+1NC in-built AUX contact,  
auto/manual reset, single phase  
prevention

	Relay range	Direct mounting on contactor	Cat ref.
 EWT015B	0.3 - 0.45 A	EW009 - EW025	EWT004B
	0.45 - 0.67 A	EW009 - EW025	EWT007B
	0.67 - 0.1 A	EW009 - EW025	EWT010B
	1.0 - 1.5 A	EW009 - EW025	EWT015B
	1.4 - 2.1 A	EW009 - EW025	EWT021B
	1.8 - 2.7 A	EW009 - EW025	EWT027B
	2.4 - 3.6 A	EW009 - EW025	EWT036B
	3.5 - 5.0 A	EW009 - EW025	EWT050B
	4.0 - 6.0 A	EW009 - EW025	EWT060B
	5.5 - 8.5 A	EW009 - EW025	EWT085B
 EWT132C	8.5 - 12.5 A	EW009 - EW025	EWT112B
	12.5 - 18 A	EW009 - EW025	EWT118B
	17 - 24 A	EW009 - EW025	EWT124B
	22 - 30 A	EW009 - EW025	EWT130B
	17-25 A	EW032 - EW040	EWT125C
	23-32 A	EW 032 - EW040	EWT132C
	30-40 A	EW 032 - EW040	EWT140C
	17-25 A	EW 050 - EW070	EWT125D
	23 - 32 A	EW 050 - EW070	EWT132D
	30- 40 A	EW 050 - EW070	EWT140D
	37 - 50 A	EW 050 - EW070	EWT150D
	48 - 65 A	EW 050 - EW070	EWT165D
	63 - 80 A	EW 050 - EW070	EWT180D

Accessories

	Relay range	Contact configuration	Cat ref.
 EWA001	<b>Auxillary contact</b> Top mounting on contactor EW009 to EW070	1 NO + 1 NC	EWA001
		2 NO	EWA002
		2 NC	EWA003
		4 NO	EWA004
		4 NC	EWA005
 EWA007	Side mounting on contactor EW009 to EW040	3 NO + 1 NC	EWA006
		2 NO + 2 NC	EWA007
		1 NO + 3 NC	EWA008
		1 NO + 1 NC	EWA009
 EWA101	Side mounting on contactor EW100 to EW300	1 NO + 1 NC	EWA010
 EWA102	<b>Mechanical interlock</b> For contactor EW009 - EW025 For contactor EW032 - EW070		EWA101 EWA103
	<b>Mechanical / Electrical interlock</b> For contactor EW009 - EW025		EWA102



**Description**

For use as a switch  
disconnecter in all types of  
circuit.

Complies with : BS EN 60 947-3  
all ratings

**Technical data**  
**utilisation category**  
AC 22B  
AC 21B for 125A

**In : 16, 25, 32A**

Shrouded cable clamps  
connection capacity:  
16mm<sup>2</sup> rigid conductor  
10mm<sup>2</sup> flexible conductor

**In : 40, 63A**

Cable clamps,  
connection capacity:  
25mm<sup>2</sup> rigid conductor  
16mm<sup>2</sup> flexible conductor



**In : 80A, 125A**

Cable clamps  
connection capacity:  
50mm<sup>2</sup> rigid conductor  
35mm<sup>2</sup> flexible conductor  
All switches have a green / red  
indication on the handle giving  
positive contact indication.

Use MZN175 as locking device





SB 140

Designation	Characteristics	Width in 17,5mm	Cat ref.
<b>Single pole</b>  	16A	1	<b>SB 116</b>
	16A with pilot light	1	<b>SB 116V</b>
	25A	1	<b>SB 125</b>
	25A with pilot light	1	<b>SB 125V</b>
	32A	1	<b>SB 132</b>
	32A with pilot light	1	<b>SB 132V</b>
	40A	1	<b>SB 140</b>
	63A	1	<b>SB 163</b>
	80A	1	<b>SB 180</b>
	100A	1	<b>SB 199</b>





SB 240

<b>Double pole</b>  	16A	1	<b>SB 216</b>
	16A with pilot light	1	<b>SB 216V</b>
	25A	1	<b>SB 225</b>
	25A with pilot light	1	<b>SB 225V</b>
	32A	1	<b>SB 232</b>
	32A with pilot light	1	<b>SB 232V</b>
	40A	2	<b>SB 240</b>
	63A	2	<b>SB 263</b>
	80A	2	<b>SB 280</b>
	100A	2	<b>SB 299</b>
	125A	2	<b>SB 212</b>



SB 363

<b>Triple pole</b> 	16A	2	<b>SB 316</b>
	25A	2	<b>SB 325</b>
	32A	2	<b>SB 332</b>
	32A large terminals	3	<b>SB 332Q</b>
	40A	3	<b>SB 340</b>
	63A	3	<b>SB 363</b>
	63A large terminals	3	<b>SB 363Q</b>
	80A	3	<b>SB 380</b>
	100A	3	<b>SB 399</b>
	125A	3	<b>SB 312</b>

Designation	Characteristics	Width in 17,5mm	Cat. ref. neutral left	Cat. ref. neutral right
<b>Four pole</b> 	16A	2	<b>SB 416F</b>	<b>SB 416</b>
	25A	2	<b>SB 425F</b>	<b>SB 425</b>
	32A	2	<b>SB 432F</b>	<b>SB 432</b>
	40A	4	<b>SB 440F</b>	<b>SB 440</b>
	63A	4	<b>SB 463F</b>	<b>SB 463</b>
	80A	4	<b>SB 480F</b>	<b>SB 480</b>
	100A	4	<b>SB 499F</b>	<b>SB 499</b>
	125A	4	<b>SB 412F</b>	<b>SB 412</b>

- Technical characteristics:**
- Voltage range -20% to +10%:  
230 - 400 V
  - Vmax: 254 - 440 V
  - Frequency: 50 / 60 Hz
  - IP rating: IP 2X

Range	MW	MU	NC	MT	MB	MV
Breaking capacity IEC 898 (kA)	3	6	10	6	6	3
Breaking capacity IEC 947-2 (kA)		10	15	10	10	
Auxiliaries	no	no	yes	no	yes	no
Tripping curve	C	C	C	B	B	B



NC110A



MU220A



MB316A



MB432A

Designation	In /A	cat. ref.	cat. ref.	cat. ref.	cat.ref.	cat. ref.	cat. ref.
Single Pole	0,5			NC100A			
	1			NC101A			
	2			NC102A			
	4			NC104A			
	6	MW106	MU106A	NC106A	MT106A	MB106A	MV106A
	10	MW110	MU110A	NC110A	MT110A	MB110A	MV110A
	16	MW116	MU116A	NC116A	MT116A	MB116A	MV116A
	20	MW120	MU120A	NC120A	MT120A	MB120A	MV120A
	25	MW125	MU125A	NC125A	MT125A	MB125A	MV125A
	32	MW132	MU132A	NC132A	MT132A	MB132A	MV132A
	40	MW140	MU140A	NC140A	MT140A	MB140A	MV140A
	50		MU150A	NC150A	MT150A	MB150A	
	63		MU163A	NC163A	MT163A	MB163A	
Double Pole	0,5			NC200A			
	1			NC201A			
	2			NC202A			
	4			NC204A			
	6	MW206	MU206A	NC206A	MT206A	MB206A	MV206A
	10	MW210	MU210A	NC210A	MT210A	MB210A	MV210A
	16	MW216	MU216A	NC216A	MT216A	MB216A	MV216A
	20	MW220	MU220A	NC220A	MT220A	MB220A	MV220A
	25	MW225	MU225A	NC225A	MT225A	MB225A	MV225A
	32	MW232	MU232A	NC232A	MT232A	MB232A	MV232A
	40	MW240	MU240A	NC240A	MT240A	MB240A	MV240A
	50		MU250A	NC250A	MT250A	MB250A	
	63		MU263A	NC263A	MT263A	MB263A	
Triple Pole	0,5			NC300A			
	1			NC301A			
	2			NC302A			
	4			NC304A			
	6	MW306	MU306A	NC306A	MT306A	MB306A	MV306A
	10	MW310	MU310A	NC310A	MT310A	MB310A	MV310A
	16	MW316	MU316A	NC316A	MT316A	MB316A	MV316A
	20	MW320	MU320A	NC320A	MT320A	MB320A	MV320A
	25	MW325	MU325A	NC325A	MT325A	MB325A	MV325A
	32	MW332	MU332A	NC332A	MT332A	MB332A	MV332A
	40	MW340	MU340A	NC340A	MT340A	MB340A	MV340A
	50		MU350A	NC350A	MT350A	MB350A	
	63		MU363A	NC363A	MT363A	MB363A	
Four pole	0,5			NC400A			
	1			NC401A			
	2			NC402A			
	4			NC404A			
	6	MW406	MU406A	NC406A	MT406A	MB406A	MV406A
	10	MW410	MU410A	NC410A	MT410A	MB410A	MV410A
	16	MW416	MU416A	NC416A	MT416A	MB416A	MV416A
	20	MW420	MU420A	NC420A	MT420A	MB420A	MV420A
	25	MW425	MU425A	NC425A	MT425A	MB425A	MV425A
	32	MW432	MU432A	NC432A	MT432A	MB432A	MV432A
	40	MW440	MU440A	NC440A	MT440A	MB440A	MV440A
	50		MU450A	NC450A	MT450A	MB450A	
	63		MU463A	NC463A	MT463A	MB463A	

## Technical characteristics:

- Voltage range -20% to +10%:  
- MC/NCN/NDN/NR: 230 - 400V  
- HLF/HMC: 240 - 415 V

- Vmax: 254 - 440 V
- Frequency: 50 / 60 Hz
- IP rating: IP 2X
- Auxiliaries

Range	MC	NCN	NDN	NRN	HLF	HMC
Breaking capacity IEC 898 (kA)	6	10	10			
Breaking capacity IEC 947-2 (kA)	10	15	15	25 (20A) 20 (25-40A) 15 (50-63A)	10	15
Tripping curve	C	C	D	C	C	C



MC106A



NCN220A



NDN320A



HLF399S

Designation	In /A	cat. ref.	cat. ref.	cat. ref.	cat. ref.	cat. ref.	cat. ref.
<b>Single Pole</b>							
0,5	MC100A	NCN100A	NDN100A	NRN100			
1	MC101A	NCN101A	NDN101A	NRN101			
2	MC102A	NCN102A	NDN102A	NRN102			
4	MC104A	NCN104A	NDN104A	NRN104			
6	MC106A	NCN106A	NDN106A	NRN106			
10	MC110A	NCN110A	NDN110A	NRN110			
16	MC116A	NCN116A	NDN116A	NRN116			
20	MC120A	NCN120A	NDN120A	NRN120			
25	MC125A	NCN125A	NDN125A	NRN125			
32	MC132A	NCN132A	NDN132A	NRN132			
40	MC140A	NCN140A	NDN140A	NRN140			
50	MC150A	NCN150A	NDN150A	NRN150			
63	MC163A	NCN163A	NDN163A	NRN163			
80*					HLF180S	HMC180	
100*					HLF190S	HMC190	
125*					HLF199S	HMC199	
<b>Double Pole</b>							
0,5	MC200A	NCN200A	NDN200A	NRN200			
1	MC201A	NCN201A	NDN201A	NRN201			
2	MC202A	NCN202A	NDN202A	NRN202			
4	MC204A	NCN204A	NDN204A	NRN204			
6	MC206A	NCN206A	NDN206A	NRN206			
10	MC210A	NCN210A	NDN210A	NRN210			
16	MC216A	NCN216A	NDN216A	NRN216			
20	MC220A	NCN220A	NDN220A	NRN220			
25	MC225A	NCN225A	NDN225A	NRN225			
32	MC232A	NCN232A	NDN232A	NRN232			
40	MC240A	NCN240A	NDN240A	NRN240			
50	MC250A	NCN250A	NDN250A	NRN250			
63	MC263A	NCN263A	NDN263A	NRN263			
80*					HLF280S	HMC280	
100*					HLF290S	HMC290	
125*					HLF299S	HMC299	
<b>Triple Pole</b>							
0,5	MC300A	NCN300A	NDN300A	NRN300			
1	MC301A	NCN301A	NDN301A	NRN301			
2	MC302A	NCN302A	NDN302A	NRN302			
4	MC304A	NCN304A	NDN304A	NRN304			
6	MC306A	NCN306A	NDN306A	NRN306			
10	MC310A	NCN310A	NDN310A	NRN310			
16	MC316A	NCN316A	NDN316A	NRN316			
20	MC320A	NCN320A	NDN320A	NRN320			
25	MC325A	NCN325A	NDN325A	NRN325			
32	MC332A	NCN332A	NDN332A	NRN332			
40	MC340A	NCN340A	NDN340A	NRN340			
50	MC350A	NCN350A	NDN350A	NRN350			
63	MC363A	NCN363A	NDN363A	NRN363			
80*					HLF380S	HMC380	
100*					HLF390S	HMC390	
125*					HLF399S	HMC399	
<b>Four Pole</b>							
0,5	MC400A	NCN400A	NDN400A	NRN400			
1	MC401A	NCN401A	NDN401A	NRN401			
2	MC402A	NCN402A	NDN402A	NRN402			
4	MC404A	NCN404A	NDN404A	NRN404			
6	MC406A	NCN406A	NDN406A	NRN406			
10	MC410A	NCN410A	NDN410A	NRN410			
16	MC416A	NCN416A	NDN416A	NRN416			
20	MC420A	NCN420A	NDN420A	NRN420			
25	MC425A	NCN425A	NDN425A	NRN425			
32	MC432A	NCN432A	NDN432A	NRN432			
40	MC440A	NCN440A	NDN440A	NRN440			
50	MC450A	NCN450A	NDN450A	NRN450			
63	MC463A	NCN463A	NDN463A	NRN463			
80*					HLF480S	HMC480	
100*					HLF490S	HMC490	
125*					HLF499S	HMC499	

\* each pole is 1.5 module width



Technical characteristics:

- standards: IEC 61008-1
  - operational voltage:  
127-230V (2 poles)  
tolerance -6 / +10%  
230-400V (4 poles)  
tolerance -6 / +10%  
Vmax: 254 / 440V
- current ratings: 16A - 100A
  - poles: 2P / 4P
  - sensitivity: 10mA / 30mA / 100mA / 300mA / 500mA
  - IP rating: IP 2X
- earth fault indication
  - On - Off indication
  - clip on busbar facility
  - selective (S) version  
(time delayed)
  - accessories:  
only for CxxxxJ version:



CD241J

Designation	In /A	10mA cat. ref.	30mA cat. ref.	100mA cat. ref.	300mA cat.ref.	500mA cat. ref.
2 poles 50 Hz	16	CC217J	-	-	-	-
	25	-	CD226J	CE226J	CF226J	-
	40	-	CD241J	CE241J	CF241J	-
	63	-	CD264J	CE264J	CF264J	-
	80	-	CD281Z	CE281Z	CF281Z	-
	100	-	CD285Z	CE285Z	CF285Z	-
	63	-	-	-	CP265F	-



CD441J

4 pole 50 Hz	25	-	CD426J	CE426J	CF426J	-
	40	-	CD441J	CE441J	CF441J	-
	63	-	CD464J	CE464J	CF464J	-
	80	-	CD480Z	CE481Z	CF481Z	CG481Z
	100	-	CD485Z	CE485Z	CF485Z	CG485Z
	40A	-	-	-	CP441J	-
	63A	-	-	-	CP464J	-

RCCBs - 60 Hz



CD225S

2 pole 60 Hz	25	-	CD225S	-	CF225S	-
	40	-	CD240S	-	CF240S	-
	63	-	CD263S	-	CF263S	-
	80	-	CD280S	-	CF280S	-
	100	-	CD284S	-	CF284S	-



CD463S

4 pole 60 Hz	25	-	CD425S	-	CF425S	-
	40	-	CD440S	-	CF440S	-
	63	-	CD463S	-	CF463S	-
	80	-	CD480S	-	CF480S	-
	100	-	CD484S	-	CF484S	-

# RCBOs 1 module type AC - C curve



**Technical characteristics:**

- standards: IEC 61009
- operational voltage: 110-230V (1 pole)  
tolerance -6 / +10%  
Vmax: 254V
- current ratings: 6A - 50A
- sensitivity: 30mA / 100mA / 300mA

- breaking capacity as per IEC 898: 6kA / 10kA
- Tripping curves as per IEC 61009: C
- frequency: 50 / 60 Hz
- IP rating: IP 2X

- indications: On - Off indication
- flying neutral lead: 700 mm
- selective (S) version



AD110Z

Designation	In /A	30mA cat. ref.	100mA cat. ref.	300mA cat. ref.
6 kA	6	AD106Z	AE106Z	-
	10	AD110Z	AE110Z	-
	16	AD116Z	AE116Z	-
	20	AD120Z	AE120Z	AF120Z
	25	AD125Z	AE125Z	AF125Z
	32	AD132Z	AE132Z	AF132Z
	40	AD140Z	AE140Z	AF140Z
	50	AD128	-	-
	<div>S</div> 50	-	AN150Z	AP150Z
10 kA	6	AD184	-	-
	10	AD185	-	-
	16	AD187	-	-
	20	AD188	-	-
	25	AD189	-	-
	32	AD190	-	-
	40	AD191	-	-

# RCBOs 2 module type AC - C curve

**Technical characteristics:**

- standards: IEC 61009
- operational voltage: 110-230V  
tolerance -6 / +10%  
Vmax: 254V
- current ratings: 6A - 40A
- sensitivity: 30mA / 300mA

- IP rating: IP 2X
- indications of earth fault
- breaking capacity: 4,5kA / 6kA
- 60HZ RCBO  
breaking capacity  
4.5 KA (IEC 898)  
6KA (IEC 947)




AD866J

Designation	In /A	30mA, 4.5kA cat. ref.	30mA, 6kA cat. ref.	300mA, 6kA cat. ref.
RCBO type AC 50HZ	6	AD856J	AD956B	AF956B
	10	AD860J	AD960B	AF960B
	16	AD866J	AD966B	AF966B
	20	AD870J	AD970B	AF970B
	25	AD875J	AD975B	AF975B
	32	AD882J	AD982B	AF982B
	40	AD890J	AD990B	AF990B
RCBO type AC 60HZ	6	ADC813F		
	10	ADC817F		
	16	ACD823F		
	20	ACD827F		
	25	ADC833F		
	32	ADC839F		
	40	ADC847F		


# RCD add-on blocks - type AC for MB, MC, NC, NCN, NDN, and NRN ranges



BD264



BF364



BD464

Designation	Sensitivity	In/A	Width in 17,5mm	C curve cat.ref.
<b>2 poles add-on blocks</b>	10mA	25A	2	<b>BC226</b>
		30mA	2	<b>BD226</b>
		40A	2	<b>BD241</b>
		63A	2	<b>BD264</b>
	100mA	63A	2	<b>BE264</b>
		25A	2	<b>BF226</b>
	300mA	40A	2	<b>BF241</b>
		63A	2	<b>BF264</b>
	100mA	63A	2	<b>BN264</b>
	300mA	63A	2	<b>BP264</b>
	1A	63A	2	<b>BS264</b>
<b>3 poles add-on blocks</b>	30mA	25A	2	<b>BD326</b>
		40A	3	<b>BD341</b>
		63A	3	<b>BD364</b>
	300mA	25A	2	<b>BF326</b>
		40A	3	<b>BF341</b>
		63A	3	<b>BF364</b>
	300mA	63A	3	<b>BP364</b>
	1A	63A	3	<b>BS364</b>
<b>4 poles add-on blocks</b>	30mA	25A	2	<b>BD426</b>
		40A	3	<b>BD441</b>
		63A	3	<b>BD464</b>
	100mA	63A	3	<b>BE464</b>
		25A	2	<b>BF426</b>
	300mA	40A	3	<b>BF441</b>
		63A	3	<b>BF464</b>
	100mA	63A	3	<b>BN464</b>
	300mA	63A	3	<b>BP464</b>
	1A	63A	3	<b>BS464</b>

## Auxiliaries and accessories for MCBs and RCCBs



MZ201



MZ204

Designation	Characteristics	Width in 17,5mm	Cat.ref.
<b>Auxiliary contact 6A 230V</b>	1NO +1NC aux. contact for indication of the main contact status	1/2	<b>MZ201</b>
<b>Alarm contact 6A 230V</b>	SD contact indicates tripping on fault	1/2	<b>MZ202</b>
<b>Shunt trip</b>	allows remote tripping of the device		
	- 230 - 415V AC	1	<b>MZ203</b>
	- 110 - 130V DC		
<b>Under voltage release</b>	- 24 - 48V AC	1	<b>MZ204</b>
	- 12 - 48V DC		
	allows MCB to be closed only when voltage is above 70% Un		
	MCB will automatically trip when voltage falls below 35% Un		
<b>Aux. and alarm contact</b>	- 48V DC	1	<b>MZ205</b>
	- 230V AC	1	<b>MZ206</b>
	dedicated to RCCBs	1	<b>CZ001</b>
<b>Locking kit</b>	also acts as RCCB interface with standard MCB auxiliaries		
	MZ203 - MZ206		
<b>Locking kit</b>	allows padlocking of the device		<b>MZN175</b>

For selection of auxiliaries combinations, please refer to the main catalogue.





LS401



LS703

Designation	L31 8,5x31,5mm	L38 10,3x38mm	L51 14x51mm	L51 14x51mm	L58 22x58mm	L58 22x58mm
<b>Single pole</b>						
1 Phase	<b>LS401</b>	<b>LS501</b>	<b>LS601*</b>	<b>LR601</b>	<b>LS701*</b>	<b>LR701</b>
1 Phase + ind. light	<b>LS431</b>	<b>LS531</b>	<b>LS601*+LS672</b>		<b>LS701*+LS672</b>	
<b>Double pole</b>						
1 Phase + Neutral	<b>LS412</b>	<b>LS512</b>	<b>LS612*</b>	<b>LR612</b>	<b>LS712*</b>	<b>LR712</b>
1 Phase + Neutral + ind. light (1 module)	<b>L43201</b>	<b>L53201</b>				
1 Phase + Neutral + ind. light			<b>LS612*+LS672</b>		<b>LS712*+LS672</b>	
1 Phase + Neutral (1 module)	<b>L40600</b>	<b>L50600</b>				
2 Phases	<b>LS402</b>	<b>LS502</b>	<b>LS602*</b>	<b>LR602</b>	<b>LS702*</b>	<b>LR702</b>
<b>Triple pole</b>						
3 Phases	<b>LS403</b>	<b>LS503</b>	<b>LS603*</b>	<b>LR603</b>	<b>LS703*</b>	<b>LR703</b>
<b>Four poles</b>						
3 Phases + Neutral	<b>LS404</b>	<b>LS504</b>	<b>LS604*</b>	<b>LR604</b>	<b>LS704*</b>	<b>LR704</b>

\* Possibility to mount accessories

Fuse links

<b>Cylindrical fuses type aM</b> protection for motor application against short circuits L38, L51, L58	<b>Cylindrical fuses type gG</b> protection for general purpose application against overload & short circuits L38, L51, L58	<b>Standard:</b> EN/IEC 60269-1, EN/IEC 60269-2
--	---	---

Designation		In /A	Cat. Ref. Type aM	Cat. Ref. Type gG
<b>Cylindrical fuses</b>				
	type aM 10 x 38 mm (L38) 500V~ (from 0.5A to 16A) 400V~ (from 20A to 32A)	0.5 A	LF300M	LF300G
		1 A	LF301M	LF301G
		2 A	LF302M	LF302G
		4 A	LF304M	LF304G
		6 A	LF306M	LF306G
		8 A	LF308M	LF308G
		10 A	LF310M	LF310G
		12 A	LF312M	LF312G
		16 A	LF316M	LF316G
		20 A	LF320M	LF320G
	type gG 10 x 38 mm (L38) 500V~ (from 0.5A to 25A) 400V~ (32A)	25 A	LF325M	LF325G
		32 A	LF332M	LF332G
		<b>Cylindrical fuses</b>		
		2 A	LF402M	LF402G
		4 A	LF404M	LF404G
		6 A	LF406M	LF406G
		8 A	LF408M	LF408G
		10 A	LF410M	LF410G
		12 A	LF412M	LF412G
		16 A	LF416M	LF416G
	type aM 14 x 51 mm (L51) 690V~ (from 2A to 25A) 500V~ (from 32A to 45A) 400V~ (50A)	20 A	LF420M	LF420G
		25 A	LF425M	LF425G
		32 A	LF432M	LF432G
		40 A	LF440M	LF440G
		45 A	LF445M	LF445G
		50 A	LF450M	LF450G
		<b>Cylindrical fuses</b>		
		16 A	LF516M	LF516G
		20 A	LF520M	LF520G
		25 A	LF525M	LF525G
	type gG 22 x 58 mm (L58) 690V~ (from 16A to 63A) 500V~ (from 80A to 100A) 400V~ (125A)	32 A	LF532M	LF532G
		40 A	LF540M	LF540G
		50 A	LF550M	LF550G
		63 A	LF563M	LF563G
		80 A	LF580M	LF580G
		100 A	LF590M	LF590G
		125 A	LF599M	LF599G

- Technical characteristics:**
  - Voltage range : 230V +/- 20%
  - Network voltage: 50 to 700 V
  - Frequency: 50 / 60 Hz
  - Working temperature: -10 to +55°C
  - Storage temperature: -25 to +70°C
- Max. cable lenght to torroids: 25m non-twisted cable 0,5 to 1,5mm2
  - 50m twisted cable
  - Standards: IEC 60755, IEC 947-2 annex B, IEC 61543, IEC 61008-1



HR 520





HR525



HR440

Designation	Characteristics	Power absorbed	Positive safety contact	Cat. ref.
Earth leakage relays non adjustable	fixed:0,03A instantaneous tripping	3VA		HR500
	fixed:0,3A instantaneous tripping	3VA		HR502
Earth leakage relays adjustable	adjustable: 0,03-0,1-0,3-0,5-1-3-10A adjustable delay: 0-0,1-0,3-0,4-0,5-1-3 50% pre alarm output	5VA	1 C/O	HR510
	adjustable: 0,03-0,1-0,3-0,5-1-3-10A adjustable delay: 0-0,1-0,3-0,4-0,5 s-1-3 s 50% pre alarm output bargraph	5VA	1 C/O	HR520
	adjustable: 0,5-1-3-5-10-20-30A adjustable delay: 0-0,1-0,2-0,25-0,3-0,4-0,5 s 50% pre alarm output bargraph	5VA	1 C/O	HR523
Earth leakage relays adjustable LCD type	adjustable: 0,03-0,1-0,3-0,5-1-3-5-10-30A adjustable delay: 0-0,1-0,3-0,4-0,5-1-3-5-10 s 1 channel	6VA	1 C/O	HR525
	adjustable: 0,03-0,1-0,3-0,5-1-3-10-30A adjustable delay: 0-0,1-0,3-0,4-0,5-1-3 s 4 channel	6VA	1 C/O	HR534
Earth leakage relays with integrated torroids	adjustable: 0,03-0,1-0,3-0,5-1-3A adjustable delay: 0-0,1-0,3-0,4-0,5-0,75-1 s			
	with integrated torroid Ø 25mm	5VA		HR440
	with integrated torroid Ø 35mm	5VA		HR441

- Technical characteristics:**
  - Frequency: 50 / 60 Hz
  - Working temperature: -10 to +55°C
- Storage temperature: -25 to +70°C
  - IP rating: IP 41

	Designation	Characteristics	Cat. ref.
 HR742	Circular torroids	Internal Ø35 mm	HR741
		Internal Ø70 mm	HR742
		Internal Ø105 mm	HR743
		Internal Ø140 mm	HR744
		Internal Ø210 mm	HR745
 HR820	Open rectangular torroids	20 x 30 mm	HR820
		50 x 80 mm	HR821
		80 x 80 mm	HR822
		80 x 120 mm	HR823
		80 x 160 mm	HR824
 HR831	Rectangular torroids	75 x 175 mm	HR830
		115 x 305 mm	HR831
		150 x 350 mm	HR832

Contactors

Contactors are essential switching devices to control heating, lighting & ventilation systems. They are recommended in association with control and energy management devices like thermostats, Time switches, PIRs sensors etc.



ESC425

Humfree contactors

The humfree versions are recommended for application where silent operating is required.

Override contactors

The override contactors are equipped with 3 position manual control button

- permanent ON
- automatic mode
- permanent OFF

Complies with IEC 61095

Auxiliary contact

1NO+1NC for remote signaling not compatible with ESC225S.

Heat dissipation insert LZ060

- Recommended to use heat dissipation insert LZ060 between group of 3 contactors.

Designation	Rated Current		Main contacts	Coil	Width in 17.5mm	Cat. ref.
	AC1	AC3				
Contactors	25A-250V	8.5A	1NO	230VAC 50/60Hz	1	ESC125
	25A-250V	8.5A	1NC	230VAC 50/60Hz	1	ESC126
	25A-250V	8.5A	2NO	230VAC 50/60Hz	1	ESC225
	25A-250V	8.5A	2NC	230VAC 50/60Hz	1	ESC226
	25A-250V	8.5A	1NO+1NC	230VAC 50/60Hz	1	ESC227
	25A-440V	8.5A	3NO	230VAC 50/60Hz	2	ESC325
	25A-440V	8.5A	4NO	230VAC 50/60Hz	2	ESC425
	25A-440V	8.5A	4NC	230VAC 50/60Hz	2	ESC426
	25A-440V	8.5A	2NO+2NC	230VAC 50/60Hz	2	ESC427
	40A-440V	25A	2NO	230VAC 50Hz	3	ESC240
	40A-440V	25A	2NC	230VAC 50Hz	3	ESC241
	40A-440V	25A	3NO	230VAC 50Hz	3	ESC340
	40A-440V	25A	4NO	230VAC 50Hz	3	ESC440
	40A-440V	25A	4NC	230VAC 50Hz	3	ESC441
	40A-440V	25A	2NO+2NC	230VAC 50Hz	3	ESC442
	63A-440V	32A	2NO	230VAC 50Hz	3	ESC263
	63A-440V	32A	2NC	230VAC 50Hz	3	ESC264
	63A-440V	32A	3NO	230VAC 50Hz	3	ESC363
	63A-440V	32A	4NO	230VAC 50Hz	3	ESC463
	63A-440V	32A	4NC	230VAC 50Hz	3	ESC464
	63A-440V	32A	2NO+2NC	230VAC 50Hz	3	ESC465



ESC463S

Hum-free contactors

Hum-free contactors	25A-250V	8.5A	2NO	220VDC, 230VAC 50/60Hz	1	ESC225S
	25A-440V	8.5A	3NO	220VDC, 230VAC 50/60Hz	2	ESC325S
	25A-440V	8.5A	4NO	220VDC, 230VAC 50/60Hz	2	ESC425S
	25A-440V	8.5A	4NC	220VDC, 230VAC 50/60Hz	3	ESC426S
	25A-440V	8.5A	2NO+2NC	220VDC, 230VAC 50/60Hz	2	ESC427S
	40A-440V	25A	2NO	220VDC, 230VAC 50/60Hz	3	ESC240S
	40A-440V	25A	3NO	220VDC, 230VAC 50/60Hz	3	ESC340S
	40A-440V	25A	4NO	220VDC, 230VAC 50/60Hz	3	ESC440S
	63A-440V	32A	2NO	220VDC, 230VAC 50/60Hz	3	ESC263S
	63A-440V	32A	3NO	220VDC, 230VAC 50/60Hz	3	ESC363S
	63A-440V	32A	4NO	220VDC, 230VAC 50/60Hz	3	ESC463S

Accessories

Auxiliary contact (1NO + 1NC)  
Heat dissipation insert

ESC080\*  
LZ060

Note : A. Override contactors are available on request  
B. Other coil voltages like 8/12V, 24V, 110/127V available on request  
\* Not compatible with ESC 225S

**Technical characteristics**

- Standards: EN 60730
- Operating voltage: 230V AC (+10/-15%), 50/60 Hz
- \*110-230V AC - 48V DC, 50/60 Hz for EH715 and EH716

- Contact rating: 16A 230V AC1
- Programming configuration: daily / weekly / daily + weekly
- Versions with power reserve
- DIN mountable



EH010



EH111

<i>Designation</i>	<i>Operating cycle</i>	<i>Power fail reserve</i>	<i>No. of channels</i>	<i>Width in 17,5 mm</i>	<i>Cat. ref.</i>
<b>Analog time switches (din rail)</b>					
Daily dial without reserve	24hrs		1	1	<b>EH010</b>
Daily dial with reserve: 200h	24hrs	200hrs	1	1	<b>EH011</b>
Daily dial without reserve	24hrs		1	3	<b>EH110</b>
Daily dial with reserve: 200h	24hrs	200hrs	1	3	<b>EH111</b>
Weekly dial with reserve	7 d	200hrs	1	3	<b>EH171</b>
Daily+weekly dial with reserve	7d/24hrs	200hrs	1	5	<b>EH191</b>

**Analog time switches (72x72mm)**

Daily dial without reserve	24hrs		1		<b>EH710</b>
Daily dial with reserve	24hrs	200hrs	1		<b>EH711</b>
Weekly dial without reserve	7d		1		<b>EH770</b>
Weekly dial with reserve	7d	200hrs	1		<b>EH771</b>
Daily dial without reserve (eco. version)	24hrs		1		<b>EH712</b>
Daily dial without reserve	24hrs		1		<b>EH715*</b>
Daily dial with reserve	24hrs	200hrs	1		<b>EH716*</b>

## Time switches digital version

**Technical characteristics**

- Standards: EN 60730
- Operating voltage: 230V AC 50/60 Hz
- \*\*12/24V AC/DC for EG103V,
- Contact rating: 16A 250V AC1 changeover contact

- Programming configuration: daily / weekly / daily + weekly
- Versions with power reserve
- Versions with PC programmable key
- PC interface for key and software available
- DIN mountable



EG203E



EG005

<i>Designation</i>	<i>Operating cycle</i>	<i>Power fail reserve</i>	<i>No. of channels</i>	<i>Width in 17,5mm</i>	<i>Cat. ref.</i>
<b>Digital time switches (din rail)</b>					
Daily cycle	24hrs	3years	1	1	<b>EG010</b>
Weekly cycle	7d	3years	1	1	<b>EG071</b>
<b>Key programmable digital time switches (din rail)</b>					
Weekly 1 Channel, 3 module	7d	3years	1	3	<b>EG170</b>
Basic version w/o key	7d	5years	1	2	<b>EG103B</b>
Evolution version with EG005	7d	5years	1	2	<b>EG103E</b>
Evolution version with EG005	7d	5years	1	2	<b>EG103V**</b>
Weekly 2 Channel, 3 module	7d	3years	2	3	<b>EG270</b>
Basic version w/o key	7d	5years	2	2	<b>EG203B</b>
Evolution version with EG005	7d	5years	2	2	<b>EG203E</b>
Weekly 4 Channel, 4 module	7d	3years	4	4	<b>EG403E</b>
USB interface with software					<b>EG003U</b>
Locking Key					<b>EG004</b>
Programming key for EG103x, EG203x					<b>EG005</b>
Programming key for, EG403E					<b>EG007</b>

**Technical characteristics**

- Voltage: 230V (+10/-15%),
- Frequency: 50 Hz
- Contact rating:  
16A AC1 230V  
8A AC1 230V (EE701)
- Loads: incandescent, halogen and fluorescent lamps

- Functional: lighting level:  
50 to 100 lux and 50 to 2000 lux

ON-OFF delay: 15 to 60 sec

Mounting: surface/ flush

Programmable version available



EE110



EE702

<i>Designation</i>	<i>Operating cycle</i>	<i>Power fail reserve</i>	<i>Width in 17,5 mm</i>	<i>Cat. ref.</i>
Compact-basic (fixed lux/delay) IP55				<b>EE701</b>
Compact-enhanced (adjustable) IP55				<b>EE702</b>
Modular - with surface cell			3	<b>EE100</b>
Modular - with flush cell			3	<b>EE101</b>
Modular programmable electromechanical clock with surface cell	24hrs	200hrs	5	<b>EE110</b>
Modular programmable electronic clock with surface cell, 8 preset programs	7d	3years	3	<b>EE170</b>
Modular programmable electronic clock with surface cell, freely programmable	7d	3years	3	<b>EE171</b>

## Astronomical time switches

**Technical characteristics**

- Supply Voltage: 230V AC  $\pm$  15%
- Frequency: 50/60 Hz
- Maximum load: 16A AC 1
- Loads: incandescent, halogen and fluorescent lamps

**Functional characteristics**

- Running accuracy:  $\pm$  1.5 sec/24 hr
- Astronomical time accuracy:  $\pm$  10 minutes
- Operating reserve: lithium battery 5 years back up

**Environment**

- Operating temperature: -10°C to +55°C
- Storage temperature: -20°C to +60°C
- Connection: 1- 6mm<sup>2</sup> flexible 1.5-10mm<sup>2</sup> rigid



EE180

EG005

<i>Designation</i>	<i>Operating cycle</i>	<i>Power fail reserve</i>	<i>Width in 17,5mm</i>	<i>Cat. ref.</i>
Modular astronomical time switch 1 channel	7d	5years	2	<b>EE180</b>
Modular astronomical time switch 2 channels	7d	5years	2	<b>EE181</b>
Programming key for EE180/181				<b>EG005</b>
PC interface & programming software				<b>EG003</b>

## Time lag switches

**Technical characteristics**

- Voltage: 230V (+10/-15%),
- Frequency: 50/60 Hz
- Contact rating:  
16A AC1 230V  
250V - 2300W incandescent, halogen and fluorescent lamps

- Function:  
EMN001 - standard time lag switch with adjustable delay from 30s to 10 min

EMN005 - multifunctional time lag switch with pre-warning

mode and double delay mode: 30s to 10 min or 1 hour



EMN001

<i>Designation</i>	<i>Cat. ref.</i>
Stair case time lag switch	<b>EMN001</b>
Multifunction stair case time lag switch	<b>EMN005</b>

**Description**

To provide all types of automatic control i.e. lighting, ventilation, watering, machine pre-heating, automatic door and visual audible indication, cycle control etc.

**Applications**

For timing and automation in domestic and commercial premises. The input signal can be via various switching devices

(pushbutton, latching switch, timeclock etc.) and the timed output used to control the application.

**Technical data**

Voltage range :  
12 & 24 to 48V DC  
12 & 24 to 230V AC  
Adjustable: time delay from 0.1s to 10 hours.  
LED indicator

complies with EN 60669-2-1

**Connection capacity :**






6mm² max flexible  
1.5 - 10mm² rigid



EZN 001



EZN 006

Designation	Characteristics	Width in 17.5mm	Pack qty.	Cat ref.
<b>Delay ON</b> 	1 c/o contact 8A / 230V~ AC1 time delay T : 0.1s to 10hr	1	1	<b>EZN 001</b>
<b>1 Delay OFF</b> 	1 c/o contact 8A / 230V~ AC1 time delay T : 0.1s to 10hr	1	1	<b>EZN 002</b>
<b>Adjustable time ON</b> 	1 c/o contact 8A / 230V~ AC1 time delay T : 0.1s to 10hr	1	1	<b>EZN 003</b>
<b>Timer</b> 	1 c/o contact 8A / 230V~ AC1 time delay T : 0.1s to 10hr	1	1	<b>EZN 004</b>
<b>Symmetrical flasher</b> 	1 c/o contact 8A / 230V~ AC1 time delay T : 0.1s to 10hr	1	1	<b>EZN 005</b>
<b>Multifunction</b> 6 individual functions including : D - delay on C - delay off E - adjustable time ON B - adjustable time OFF A - timer F - symmetrical flasher - ON - OFF	1 c/o contact 8A / 230V~ AC1 time delay T : 0.1s to 10hr	1	1	<b>EZN 006</b>



**Description**

For the control of lighting circuits in private buildings, small industry buildings and administration buildings. Latching relays - operate when impulsed by a signal voltage. The impulse can be provided via a pushbutton or switch. The first

pulse operates the relay and latches it into its set (opposite) state, the next operation of the pushbutton returns the relay into its reset (original) state. The latching relays are built to add on optionally the following auxiliaries :

- an auxiliary for centralised ON/OFF control EPN 050
- an auxiliary contact for remote signalling EPN 051
- an auxiliary for multi levelled centralised control EPN 052
- an auxiliary for control by maintained contact EPN 053.

**Connection capacity**

10 mm<sup>2</sup> rigid cables  
6 mm<sup>2</sup> flexible cables







Conform to standard EN669-1 and EN669-2-2



EPN 510







EPN 540

Designation	Type	Coil VAC 50/60Hz	Coil VDC	Power Circuit AC1	Width in 17.5mm	Pack qty.	Cat. ref.
<b>Latching relays</b> 	<b>1NO</b>	230	110	16A-250V	1	12	<b>EPN 510</b>
		48	24	16A-250V	1	1	<b>EPN 501</b>
		24	12	16A-250V	1	1	<b>EPN 513</b>
		12	-	16A-250V	1	1	<b>EPN 511</b>
	<b>2NO</b>	230	110	16A-250V	1	1	<b>EPN 520</b>
		110	48	16A-250V	1	1	<b>EPN 523</b>
		48	24	16A-250V	1	1	<b>EPN 526</b>
		24	12	16A-250V	1	1	<b>EPN 524</b>
		12	-	16A-250V	1	1	<b>EPN 521</b>
	<b>1NC+1NO</b>	230	110	16A-250V	1	1	<b>EPN 515</b>
		110	48	16A-250V	1	1	<b>EPN 516</b>
		48	24	16A-250V	1	1	<b>EPN 503</b>
		24	12	16A-250V	1	1	<b>EPN 518</b>
		12	-	16A-250V	1	1	<b>EPN 519</b>
	<b>4NO</b>	230	110	16A-400V	2	1	<b>EPN 540</b>
		48	24	16A-400V	2	1	<b>EPN 548</b>
		24	12	16A-400V	2	1	<b>EPN 541</b>
	<b>2NC+2NO</b>	230	110	16A-250V	2	1	<b>EPN 525</b>
		24	12	16A-250V	2	1	<b>EPN 528</b>
	<b>3NO+1NC</b>	230	110	16A-400V	2	1	<b>EPN 546</b>

Latching relays auxiliaries



EPN 052





























Designation		Voltage supply	Width in 17.5mm	Pack qty.	Cat. ref.
<b>Auxiliary for centralised control</b>		24 to 230V AC	1/2	1	<b>EPN 050</b>
<b>Auxiliary contact</b>		2A - 250 V AC	1/2	1	<b>EPN 051</b>
<b>Auxiliary for multi levelled centralised control</b>		24 to 230V AC	1/2	1	<b>EPN 052</b>
<b>Auxiliary for control by maintained contact</b>		24 to 230V AC	1/2	1	<b>EPN 053</b>

**Push buttons:**  
2 versions :  
impulse push buttons  
latching push buttons

These versions with indicator  
lights are equipped with green or  
red diffuser. (led technology)

**Connection capacity :**  
- 10mm<sup>2</sup> rigid,  
- 6mm<sup>2</sup> flexible.









**Standard conformity :**  
IEC 60947-5-1 for push buttons  
IEC 62094-1 for indicator lights

	Designation	Characteristics	Width in 17,5 mm	Pack qty.	Cat. ref.
	<b>Impulse push button</b>	16 A - 250 V ~ <b>without indicator light</b>			
		contact: 1NO	1	12	<b>SVN 311</b>
		contact: 1NC	1	12	<b>SVN 321</b>
		contacts: 2NO	1	12	<b>SVN 331</b>
		contacts: 2NC	1	12	<b>SVN 341</b>
		contacts: 1NO+1NC	1	12	<b>SVN 351</b>
		contacts: 2NO	1	12	<b>SVN 371</b>
		contacts: 1NO+1NC	1	12	<b>SVN 391</b>
		<b>with indicator light :</b> contact: 1NO green	1	12	<b>SVN 411</b>
		contact: 1NC red	1	12	<b>SVN 422</b>
		contacts: 2NO red	1	12	<b>SVN 432</b>
		contacts: 2NC green	1	12	<b>SVN 441</b>
		contacts: 1NO+1NC red	1	12	<b>SVN 452</b>
		16 A - 12/48 V AC/DC <b>with indicator light</b> contacts: 2NO green	1	12	<b>SVN461</b>
		contacts: 2 NO red	1	12	<b>SVN 462</b>
		<b>with indicator light</b> contacts: 2NO green	1	12	<b>SVN 463</b>
		contacts: 2 NO red	1	12	<b>SVN 464</b>
		<b>Latching push buttons</b>			
		16 A - 250 V ~ <b>without indicator light</b> contact: 1NO	1	12	<b>SVN 312</b>
		contact: 1NC	1	12	<b>SVN 322</b>
		contacts: 2NO	1	12	<b>SVN 332</b>
		contacts: 2NC	1	12	<b>SVN 342</b>
		contacts: 1NO+1NC	1	12	<b>SVN 352</b>
		<b>with indicator light :</b> contact: 1 NO green	1	12	<b>SVN 413</b>
		contacts: 2 NO green	1	12	<b>SVN 433</b>

**Indicator lights and push buttons**  
These products are used for remote controlling signalisation of any event in any electric installation (domestic, tertiary &

industrial)  
LED technology providing longer life, new design, integrated label holder

**Connection capacity :**  
- 10 mm<sup>2</sup> rigid  
- 6 mm<sup>2</sup> flexible  
  
**Standard conformity :**  
IEC 62094-1 for indicator lights

	Designation	Characteristics	Width in 17,5 mm	Pack qty.	Cat. ref.
 SVN 122   SVN 125   SVN 121 SVN 123   SVN 124	<b>Single indicator light</b> 230 V ~ 	with light : green	1	12	<b>SVN 121</b>
		red	1	12	<b>SVN 122</b>
		orange	1	12	<b>SVN 123</b>
		blue	1	12	<b>SVN 124</b>
		color less	1	12	<b>SVN 125</b>
 SVN 126	<b>Double indicator light</b> 230 V ~ 	with light: green and red	1	12	<b>SVN 126</b>
		color less 2x	1	12	<b>SVN 128</b>
 SVN 127	<b>Triple indicator light</b> 	with light: red	1	12	<b>SVN 127</b>
		red/orange/green	1	12	<b>SVN129</b>
		green	1	12	<b>SVN 221</b>
 SVN 127	<b>Low voltage indicator lights</b> 12 to 48 V AC/DC 	with light green	1	12	<b>SVN 131</b>
		red	1	12	<b>SVN 132</b>
		orange	1	12	<b>SVN 133</b>
		blue	1	12	<b>SVN 134</b>
		color less	1	12	<b>SVN 135</b>

Hour counters

**Technical characteristics**  
  
• Voltage: 230V 50Hz  
• Connection: in parallel to the load

	Designation	Characteristics	Width in 17.5mm	Pack qty.	Cat. ref.
	<b>Hours counter</b>	230V 50Hz	2	1	<b>EC 100</b>



EC 100

Energymeters are aimed to measure the active energy consumed by an installation. They permit to have under control the real cost of an installation and to divide the consumption between the different appliances.

- Characteristics :**
- fully compliant with the european standard EN50470-3.
  - class B.
  - accuracy 1 %
  - energy readout : 7 digits.
  - Backlighted display
  - Indication of instantaneous power consumption
  - Total / partial counter (excepted

- MID references)
- Pulsed output
  - unlimited saving of measures.
  - LED flashing according to consumption.
  - Option : tarif 1 / tarif 2.
  - Three phases energymeters are adapted to all kind of networks.
  - Display indication in case of bad wiring.



EC 051



EC 150



EC 364M



EC 370

Designation	Characteristics	Width in 17.5mm	Pack qty.	Cat. ref.
<b>Single phase</b>  - direct reading 32A	230V +/- 20% 50/60Hz			
	single tariff without pulsed output	1	1	<b>EC 050</b>
	single tariff with pulsed output	1	1	<b>EC 051</b>
<b>Single phase energymeters direct 63A</b>	230V~ 50/60 Hz starting current = 40mA base current = 10A max current = 63A			
	energymeter with pulsed output and total/partial	3	1	<b>EC150</b>
	energymeter with pulsed output total/partial counter and 2 tariffs	3	1	<b>EC152</b>
	energymeter with pulsed output with MID approval	3	1	<b>EC154M</b>
<b>Three phase energymeters direct 63A</b>	230/400V~ 50/60 Hz starting current = 40mA base current = 10A max current = 63A			
	energymeter with pulsed output and total/partial	4	1	<b>EC350</b>
	energymeter with pulsed output total/partial counter and 2 tariffs	4	1	<b>EC352</b>
<b>Three phase energymeters direct 100A</b>	230/400V~ 50/60 Hz starting current = 80mA base current = 20A max current = 100A			
	energymeter with pulsed output and total/partial	7	1	<b>EC360</b>
	energymeter with pulsed output total/partial counter and 2 tariffs	7	1	<b>EC362</b>
	energymeter with pulsed output with MID approval	7	1	<b>EC364M</b>
	energymeter with bi-directionnal counter	7	1	<b>EC365B</b>
<b>Three phase energymeters connection via current transformers</b> to be connected with CT with 5A on the secondary.	230/400V~ 50/60 Hz starting current = 10mA max current on CT secondary=6A			
	energymeter with pulsed output and total/partial	4	1	<b>EC370</b>
	energymeter with pulsed output total/partial counter and 2 tariffs	4	1	<b>EC372</b>

The Hager products are suitable for all light sources : incandescent, LV and VLV halogen, fluorescent with electronic ballast.

Dimming controlled by push button :  
- start/stop by short press  
- increasing/decreasing by maintaining pressure

**Common characteristics :**  
- Softstart (progressive start) to increase the working live of lamps  
- memorisation of last dimming level  
- protection against overheating  
- control possible by illuminated pushbutton until 5mA.

**Dimmers 600 and 1000 W :**  
- universal products with automatic recognition of the load type (inductive/capacitive)  
- electronic protection against overheating and overload  
- Indicators :  
230 V / overheating / overload



EV 004



EV 100



EV 102

Designation	Characteristics	Width in 17,5 mm	Pack qty	Cat. Ref.
<b>Universal remote control dimmer 600 W</b> - incandescent 230 V - halogen 230 V - VLV halogen lamps supplied by ferromagnetic or dimmable electronic transformer (cos $\phi \geq 0,95$ )	20 ... 600 W / VA 230 V / 50 Hz - products with automatic load recognition - dimming function	4	1	<b>EV 002</b>
<b>Universal dimmer 1000 W for :</b> • Functional mode selection via local switch : - control via pushbutton (local) - remote control via 1/10V (slave) • Min/Max setting via potentiometer • LED indication : - 230V power supply/load error - overload / overheating <b>Load type :</b> - incandescent - 230V halogen lamps - VLV halogen lamps associated to ferromagnetic transformer (inductive) - VLV halogen lamps associated to electronic transformer (capacitive)	230 V ~ / 50 Hz  20 ...1 000W  1/10V-input	5	1	<b>EV 100</b>
<b>Universal dimmer 1000 W with scene inputs</b> • Functional mode selection via local switch : - control via pushbutton (local) - remote control via 1/10V (slave) - control of the other dimmers via 1/10V (master) • Display to show the dim level and to set the parameters: - dimming rise time (4s ..99s) - min dim level (0...49%) - max dim level (51...99%) - rise time when switching ON (1s..99s) - fall time when switching OFF (1s..99s) - scene level - dimming rise time for each scene - scene working mode : recall or override mode • Output contact to display the dim state (load is OFF, contact is opened, if load is dimmed the contact is closed) • LED indication : - 230V power supply / load error - overload / overheating <b>Load type :</b> - incandescent - 230V halogen lamps - VLV halogen lamps associated to ferromagnetic transformer (inductive) - VLV halogen lamps associated to electronic transformer (capacitive)	230 V ~ / 50 Hz  20 ...1 000W  1/10V-input/output (max. 50mA, 30 EV100 / EV102) defined via the local switch  Contact output : 1 NO, 250V ~, $\mu$ 5A	5	1	<b>EV 102</b>

These devices are made for automatic control of lighting in both the residential and private/public industry sectors. They automatically switch on lighting in case a person in movement is detected and light is needed. They turn off the light after a pre-set duration.

**EE 820, EE 830, EE 840, EE825, EE 827**

- That waterproof detector range (IP55) is mainly dedicated to outdoor applications.
- They are equipped with Fresnel lenses that permit to get a high detection performance.
- Detector 140° for access control and perimeter lighting

- 200° models to survey a house facade
- 360° to cover a house corner

- The fixing accessories allow ceiling and corner mounting.
  - Settings
- The timer and the lux level are set locally, via potentiometer.



**EE 804, EE 805**

- Movement detector for the automatic control of lighting in indoor circulating zones.
- Surface mounted (EE 804) or flush fitting (EE 805).
- Setting
- The timer and the lux level are defined via potentiometers
- Mounting of EE805
- Connecting system

- conform to false ceiling installation standards (cable clamp, fixing spring and protection cover)
- Surface mounting of EE804
- Connecting on a ceiling box or on mouldings thanks to side pre-cut outs
- compatible with Tehalit ATA 63000 (6 x 30) or ATA 12200 (12x20)
- Output
- Potential free relay contact 10A

	Designation	Characteristics	Pack qty.	Cat. ref.
 EE 820	<b>Detector</b>	140° white	1	<b>EE 820</b>
	surface IP55	200° white	1	<b>EE 830</b>
	230 V ~ 50/60 Hz	360° white	1	<b>EE 840</b>
	Lux: 5 to 1000 lux			
	Timer: pulse, 5s to 15 min			
 EE 825	Contact 10A AC1			
	Corner mounting accessory	white	1	<b>EE 825</b>
	Ceiling mounting accessory	white	1	<b>EE 827</b>
 EE 804	<b>Detector 360°</b>	230 V ~ ± 10%, 50Hz	1	<b>EE 804</b>
	surface IP21 diam. 105,5 white*	Functions : - 1 open contact 10 A - detection angle 360°  Lux: 5 to 1000 lux Timer: 5 s. to 15 min.		
 EE 805	<b>Detector 360°</b>	230 V ~ ± 10%, 50Hz	1	<b>EE 805</b>
	flush IP21 diam. 105,5 white*	Functions : - 1 open contact 10 A - detection angle 360°  Lux: 5 to 1000 lux Timer: 5 s. to 15 min.		


<b>Description</b> High performance presence detector that will be used in premises or in passage areas, where they increase comfort and reduce drastically the energy costs. Settings via potentiometers or via remote control EE807	<b>EE815 - presence detector</b> ON/OFF Direct control of a light load Lux level and ON delay settings	Customer remote control EE808 for override operation.
	<b>EE816 - presence detector for light regulation</b> 3 functional modes DALI/DSI bus output	

	Designation	Characteristics	Pack qty.	Cat. ref.
 EE 816	<b>Presence detector Monobloc ON/OFF (IP41)</b> Timer: 1min to 1 hour Brightness: 5 to 1000 lux	Switched phase 16A AC1 230 V AC ~ 50/60 Hz 360° white	1	<b>EE 815</b>
	<b>Monobloc DALI/DSI (IP41)</b> For lighting regulation Timer: 1min to 1 hour Brightness: 5 to 1000 lux	DALI/DSI bus (24 ballasts) 230 V AC ~ 50/60 Hz 360° white	1	<b>EE 816</b>
 EE 807	<b>Remote control</b> (for EE815 & EE816)  For settings	Infra red remote control	1	<b>EE 807</b>
	For customer	Infra red remote control override operation	1	<b>EE 808</b>


EE 808

PIR detection - Range


Motion detectors EE 820 & EE 830




Motion detectors EE 804 & EE 805



Motion detector EE 840



Presence detectors EE 815 & EE 816



Note: The optimum height of installation is 2.5m. The detection field must remain free.



Technical characteristics

Base pre-drilled with lid.

Standard length: 2 Mtr.






Material: Rigid PVC


Colour: Grey (RAL 7030)

Fire classification : UL 94VO.


Base and lid




	Dimensions (Height x Width) in mm	Qty. per pack in Mtrs.	Cat. ref.
	25 x 25 25 x 40	50m 48m	<b>BA725025</b> <b>BA725040</b>
Height 25 mm			
	40 x 25 40 x 40 40 x 60 40 x 80 40 x 100	48m 50m 40m 30m 20m	<b>BA740025</b> <b>BA740040</b> <b>BA740060</b> <b>BA740080</b> <b>BA740100</b>
Height 40 mm			
	60 x 25 60 x 40 60 x 60 60 x 80 60 x 100 60 x 120	60m 40m 24m 20m 16m 12m	<b>BA760025</b> <b>BA760040</b> <b>BA760060</b> <b>BA760080</b> <b>BA760100</b> <b>BA760120</b>
Height 60 mm			
	80 x 25 80 x 40 80 x 60 80 x 80 80 x 100 80 x 120	20m 20m 20m 16m 12m 16m	<b>BA780025</b> <b>BA780040</b> <b>BA780060</b> <b>BA780080</b> <b>BA780100</b> <b>BA780120</b>
Height 80 mm			
	100 x 60 100 x 80 100 x 100	16m 16m 12m	<b>BA7100060</b> <b>BA7100080</b> <b>BA7100100</b>
Height 100 mm			




Dimensions  
height 25 mm  
ducting 25 x 40




Dimensions  
height 100 mm



Perforation  
details  
DIN 43659  
EN 50 085-2-3  
width 80, 100 and  
120 mm



Dimensions  
height 60 and  
80 mm



Perforation details  
DIN 43659  
EN 50 085-2-3  
width 25, 40 and  
60 mm



# New invicta type B distribution boards & panel boards

Hager has developed the new invicta Type B distribution boards as a solution for modern residential, commercial and industrial installations. The key features like the state of the art PAN assembly, incomer shrouds adds value to the installation system in terms of safety, elegance and flexibility.

The new Panel boards with the feature loaded H3 MCCBs makes the best combination in terms of value for money for the users in terms of flexibility, choice & performance. The solution is versatile with Meter boxes, DIN rail extension boxes and cable spreader boxes.

The whole range offer the best performance and ASTA certified.



VT04SM-T

Designation	No. of outgoing ways	Cat. Ref. Surface mounted	Cat. Ref. Flush mounted
<b>Consumer unit with 100A SP busbar</b>			
	4	VT04SM	VT04FM
	6	VT06SM	VT06FM
	8	VT08SM	VT08FM
	10	VT10SM	VT10FM
	12	VT12SM	VT12FM
	16	VT16SM	VT16FM



VT08MF



VT08TF

No. of modules	Door	Cat. Ref. Surface mounted	Cat. Ref. Flush mounted
<b>Consumer unit without busbar</b>			
4	Metal (non transparent)	VT04MS	VT04MF
	Opaque plastic	VT04PNS	VT04PNF
	Transparent	VT04TS	VT04TF
8	Metal (non transparent)	VT08MS	VT08MF
	Opaque plastic	VT08PNS	VT08PNF
	Transparent	VT08TS	VT08TF
12	Metal (non transparent)	VT12MS	VT12MF
	Opaque plastic	VT12PNS	VT12PNF
	Transparent	VT12TS	VT12TF
16	Metal (non transparent)	VT16MS	VT16MF
	Opaque plastic	VT16PNS	VT16PNF
	Transparent	VT16TS	VT16TF
20	Metal (non transparent)	VT20MS	VT20MF
	Opaque plastic	VT20PNS	VT20PNF
	Transparent	VT20TS	VT20TF


Invicta DIN rail distribution boards



DR32S

Designation	No. of rows	No. of Modules	Cat. Ref. Surface mounted	Cat. Ref. Flush mounted
<b>DIN Rail Distribution boards</b>				
	1	16	DR16S	DR16F
	2	32	DR32S	DR32F
	3	48	DR48S	DR48F
	4	64	DR64S	DR64F
	5	80	DR80S	DR80F
	6	96	DR96S	DR96F


Designation	Cat. Ref
<b>Accessories</b>	
Joining kits for surface boards	JK01SK
Joining kits for flush boards	JK01FK
1 mod blanking strip	P032H
Key lock	VZ303



Removable door and reversible for ease of fitting




Ease of phase identification  
L1, L2, L3 mouldings show through when the front cover is fitted. Textured surface on busbar assembly allows to write circuit identification.



Earth terminal bars are mounted offset to neutral terminal bars and angled towards the installer for easy cable installation. The screws are fully turned down for simple and fast cabling,



Top tap off for board extensions for MCBs up to 100A




Optional transparent IP2X neutral cover



Whole set of busbar separated into "circuit A & circuit B" in split load board.








Order codes for invicta split busbar boards without wire sets.

No. of ways Section A	Section B	Cat. Ref. Surface	Cat. Ref. Flush
2	2	JK1B022S2	JK1B022F2
4	2	JK1B042S2	JK1B042F2
4	4	JK1B044S2	JK1B044F2
6	2	JK1B062S2	JK1B062F2
6	4	JK1B064S2	JK1B064F2
6	6	JK1B066S2	JK1B066F2
8	4	JK1B084S2	JK1B084F2
8	6	JK1B086S2	JK1B086F2
8	8	JK1B088S2	JK1B088F2
10	4	JK1B104S2	JK1B104F2



JK1B042S2WA316

To fit up to 125A isolator 4P RCCB (Section B) and MU363A (Section A) as incomer.

No. of out going ways Section A	Section B	Cat. Ref. Surface	Cat. Ref. Flush
2	2	JK1B022S2WA216	JK1B022F2WA216
4	2	JK1B042S2WA216	JK1B042F2WA216
4	4	JK1B044S2WA216	JK1B044F2WA216
6	2	JK1B062S2WA216	JK1B062F2WA216
6	4	JK1B064S2WA216	JK1B064F2WA216
6	6	JK1B066S2WA216	JK1B066F2WA216
8	4	JK1B084S2WA216	JK1B084F2WA216
8	6	JK1B086S2WA216	JK1B086F2WA216
8	8	JK1B088S2WA216	JK1B088F2WA216
10	4	JK1B104S2WA216	JK1B104F2WA216

To fit up to 125A isolator 2 nos of 4P RCCB (Section A and B) as incomers.

No. of out going ways Section A	Section B	Cat. Ref. Surface	Cat. Ref. Flush
2	2	JK1B022S2WA316	JK1B022F2WA316
4	2	JK1B042S2WA316	JK1B042F2WA316
4	4	JK1B044S2WA316	JK1B044F2WA316
6	2	JK1B062S2WA316	JK1B062F2WA316
6	4	JK1B064S2WA316	JK1B064F2WA316
6	6	JK1B066S2WA316	JK1B066F2WA316
8	4	JK1B084S2WA316	JK1B084F2WA316
8	6	JK1B086S2WA316	JK1B086F2WA316
8	8	JK1B088S2WA316	JK1B088F2WA316
10	4	JK1B104S2WA316	JK1B104F2WA316

**Notes:**  
Incomers are not fitted and should be ordered separately

## Invicta - TPN125 type B distribution board with split busbar accessories

Designation	Cat. Ref.	
<b>Cable spreader box</b>	<b>Surface</b>	<b>Flush</b>
Cable spreader box	JK2E01S	JK2E01F
<b>DIN rail extension box</b>		
16 mod	JK2E16S	JK2E16F
32 mod	JK2E32S	JK2E32F
48 mod	JK2E48S	JK2E48F
<b>Accessories</b>		
Top & bottom gland plate with screws		JK1XGP
1 mod blank		P032H
1 mod MCB blank		JK1XBSP
Busbar protective boot		P100H
Key lock		JK1XKLS
Incomer shroud 13 mod		JK2XISS
Neutral terminal cover IP2X		JK1XNC



JK1XBSP



P032H



JK1XNC



**Technical characteristics****Standards:**

BS EN 60439 - 1 &amp; 3

Suitable for non modular  
incomers and  
modular outgoings

**ASTA certified****Busbar current rating:**

250A

- Rated short circuit withstand  
for busbars:  
20 kA at 415V for 0.2 sec.


Removable pre punched top  
and bottom gland plates.

Reversible doors.

1.2 mm thick, sheet steel RAL  
9002 epoxy powder coated en-  
closure.

IP41

Accessories like key lock, DIN  
rail extension boxes etc...



JK2B06S2

*Designation**Cat. Ref.  
Surface**Cat. Ref.  
Flush*

4 way	JK2B04S2	JK2B04F2
6 way	JK2B06S2	JK2B06F2
8 way	JK2B08S2	JK2B08F2
10 way	JK2B10S2	JK2B10F2
12 way	JK2B12S2	JK2B12F2
16 way	JK2B16S2	JK2B16F2
18 way	JK2B18S2	JK2B18F2
24 way	JK2B24S2	JK2B24F2

**Notes:**

1. I/C link kits are not supplied as standard, please order link kits separately.
2. 13mod Blank supplied with link kit to suit JK switch/MCCB incomers
3. For product references of boards with I/C fitted, please suffix the I/C product reference to the board reference.  
e.g. if JK2B04S2 to be fitted with JK200S, the new reference will be JK2B04S2JK200S.  
e.g. if JK2B04S2 to be fitted with MCCB HHA100Z, the new reference will be JK2B04S2HHA100Z.

## Invicta - TPN250 type B distribution board extensions & accessories

*Designation**Cat. Ref.***Incomer link kits**

3 pole 160A switch disconnecter (JK160S)  
3 pole 200A / 250A switch disconnecter (JK200S/JK250S)  
3 pole X160 Frame MCCB (up to 160A)  
3 pole X250 Frame MCCB (up to 250A)  
4 pole X160 Frame MCCB (up to 160A)  
4 pole X250 Frame MCCB (up to 250A)  
Direct connection kit

JK2L1603SK  
JK2L2503SK  
JK2L1603MH  
JK2L2503MH  
JK2L1604MH  
JK2L2504MH  
JK2L2504D

**Cable spreader box**

Cable spreader box

**Surface**

JK2E01S

**Flush**

JK2E01F

**DIN rail extension box**

16 mod  
32 mod  
48 mod

JK2E16S  
JK2E32S  
JK2E48S

JK2E16F  
JK2E32F  
JK2E48F

**Accessories**

Top & bottom gland plate with screws  
1 mod blank  
1 mod MCB blank  
Busbar protective boot  
Key lock  
Neutral terminal cover IP2X  
13 mod blank for 160A switch disconnecter (JK160S)  
13 mod blank for 200/250A switch disconnecter (JK250S)  
13 mod blank for X160 frame MCCB  
13 mod blank for X250 frame MCCB

JK2XGP  
P032H  
JK1XBSP  
P100H  
JK1XKLS  
JK1XNC  
JK2XBSK1  
JK2XBSK2  
JK2XBMH1  
JK2XBMH2



JK1XBSP



P032H



JK1XNC



Optimal cabling space.



Ease of phase identification  
L1, L2, L3 mouldings show through when the front cover is fitted. Textured surface on bus-bar assembly allows contractor to write circuit identification.



Earth and neutral bars positioned for easier cabling



Multiple incomer choice switch or MCCB





### Technical characteristics

#### Standards:

BS EN 60439 - 1 &amp; 3

Suitable for MCCBs incomers and outgoing.

Option for installing CTs in meterable versions.

#### ASTA certified

#### Busbar current rating:

800A


Rated short circuit withstand for busbars 40KA for 1 sec

Removable top and bottom gland plates.

1.5 mm thickness sheet steel with epoxy powder coating in RAL 9002

IP41

Accessories like key lock, DIN rail extension boxes etc...




JN8B00006S2

Description	No. of out going ways X250 frame MCCB (up to 250A)	No. of out going ways X160 frame MCCB (up to 125A)	Provision for 3 pole h630/h800 frame MCCB incomer (non-meterable)	Provision for 3 pole h630/h800 frame MCCB incomer (meterable)
<b>630A / 800A panel board</b>				
Incomer:	/	4	JN8B00004S2	/
h630 frame MCCB (up to 630A) /	/	6	JN8B00006S2	/
h800 frame MCCB (up to 800A)	/	8	JN8B00008S2	/
Outgoing:				
X160 frame MCCB (up to 125A)	/	10	JN8B00010S2	/
	/	12	JN8B00012S2	/
	/	16	JN8B00016S2	/
<b>630A / 800A panel board</b>				
Incomer:	4	/	JN8B00400S2	/
h630 frame MCCB (up to 630A) /	6	/	JN8B00600S2	/
h800 frame MCCB (up to 800A)	8	/	JN8B00800S2	/
Outgoing:				
X250 frame MCCB (up to 250A)	10	/	JN8B01000S2	/
	12	/	JN8B01200S2	/
	16	/	JN8B01600S2	/
<b>630A / 800A panel board</b>				
Incomer:				
h630 frame MCCB (up to 630A) /	2	2	JN8B00202S2	JN8B00202S3
h800 frame MCCB (up to 800A)	2	4	JN8B00204S2	JN8B00204S3
Outgoing:				
X250 frame MCCB (up to 250A)	2	6	JN8B00206S2	JN8B00206S3
+ X160 frame MCCB (up to 125A)	2	8	JN8B00208S2	JN8B00208S3
	2	10	JN8B00210S2	JN8B00210S3
	2	14	JN8B00214S2	JN8B00214S3
<b>630A / 800A panel board</b>				
Incomer:				
h630 frame MCCB (up to 630A) /	4	2	JN8B00402S2	/
h800 frame MCCB (up to 800A)	4	4	JN8B00404S2	/
Outgoing:				
X250 frame MCCB (up to 250A)	4	6	JN8B00406S2	/
+ X160 frame MCCB (up to 125A)	4	8	JN8B00408S2	/
	4	10	JN8B00410S2	/

#### Notes:

- Incomer link kits are not supplied as standard for non meterable boards,  
For link kits please refer next page.
- 3 pole h630 frame MCCB incomer link kits are supplied with the meterable boards.



JN8B00006S2

Description	No. of out going ways h400 frame MCCB (up to 400A)	No. of out going ways X250 frame MCCB (up to 250A)	No. of out going ways X160 frame MCCB (up to 125A)	Provision for 3 pole h630/h800 frame MCCB incomer (non-meterable)	Provision for 3 pole h630/h800 frame MCCB incomer (meterable)
<b>630A / 800A panel board</b>					
Incomer:	/	6	6	<b>JN8B0006S2</b>	/
h630 frame MCCB (up to 630A) / h800 frame MCCB (up to 800A)	/	6	8	<b>JN8B0006S2</b>	/
Outgoing:					
X250 frame MCCB (up to 250A) + X160 frame MCCB (up to 125A)					

## Notes:

1. Incomer link kits are not supplied as standard for non meterable boards, For link kits please refer next page.
2. 3 pole h630 frame MCCB incomer link kits are supplied with the meterable boards.

# Invicta - 630A / 800A panel board accessories

Description	Cat. Ref.
<b>Incomer Kits</b>	
3 pole h630 frame MCCB incomer	<b>JN8L6303MH</b>
630A direct incomer kit	<b>JN8L6303D</b>
3 pole h800 frame MCCB incomer	<b>JN8L8003MH</b>
800A direct incomer	<b>JN8L8003D</b>
<b>Extension box</b>	
Cable spreader box / Meter box without cutout	<b>JN8E01S</b>
Meter box with cutout (Provision for 96mm x 96mm for VM/AM, RYB indicating lamps, selector switches)	<b>JN8E02S</b>
32 mod din rail box	<b>JN8E32S</b>
<b>Accessories / spares</b>	
Key lock	<b>JK1XKLS</b>



JN8E02S

**Description**

The range of enclosed LBS have been designed to match the TP&N range of distribution boards. The number of enclosure sizes have been optimized, to ensure that the installation is easy and uniform. Products are designed to isolate individual circuits. All handles can be padlocked in the off position.

Extension boxes are available for extra cabling space. Operation is through a door operated rotary handle.

**Electrical specification**

Tested and complies to  
BS EN 60439-1 (enclosure)  
BS EN 60947-3 (device)  
LBS Sequence 1 & 3  
FCS Sequence 1 & 4

**Electrical Supply**

415V ~ AC  
Rating AC23A (100, 315, 400 & 630A AC22A)

**Mechanical specification**

Material 1.2 mm CR4 Steel  
Powder Coated RAL 9002  
IP40

**Devices & accessories**

TPN 20-1600A (14 ratings)  
TPSN 20-1600A (14 ratings)



JAB306

<i>Description</i>	<i>In A</i>	<i>Utilisation category</i>	<i>Cat. ref.</i>
<b>Triple pole and neutral</b>	20A	AC23A	<b>JAB302</b>
	32A	AC23A	<b>JAB303</b>
	63A	AC23A	<b>JAB306</b>
	100A	AC22A	<b>JAB310</b>
	125A	AC23A	<b>JAC312</b>
	160A	AC23A	<b>JAC316</b>
	200A	AC23A	<b>JAE320</b>
	250A	AC23A	<b>JAE325</b>
	315A	AC22A	<b>JAG331</b>
	400A	AC22A	<b>JAG340</b>
	630A	AC22B	<b>JAH363</b>
	800A	AC23B	<b>JAH380</b>
	1250A	AC23A	<b>JAH390</b>
	1600A	AC23A	<b>JAH392</b>
<b>Triple pole switched neutral</b>	20A	AC23A	<b>JAB402</b>
	32A	AC23A	<b>JAB403</b>
	63A	AC23A	<b>JAB406</b>
	100A	AC22A	<b>JAB410</b>
	125A	AC23A	<b>JAC412</b>
	160A	AC23A	<b>JAC416</b>
	200A	AC23A	<b>JAE420</b>
	250A	AC23A	<b>JAE425</b>
	315A	AC22A	<b>JAG431</b>
	400A	AC22A	<b>JAG440</b>
	630A	AC22B	<b>JAH463</b>
	800A	AC23B	<b>JAH480</b>
	1250A	AC23A	<b>JAH490</b>
	1600A	AC23A	<b>JAH492</b>
<b>Cable extension boxes triple pole and triple pole switched neutral</b>	125A, 160A		<b>JZA700</b>
	200A, 250A, 315A, 400A		<b>JZA701</b>
	630A, 800A		<b>JZA702</b>
<b>Auxiliary contact 1NO+1NC</b>	20A to 63A		<b>HZ021</b>
	100A to 160A		<b>HZ022</b>
	200A to 630A		<b>HZ023</b>
	800A to 1600A		<b>HZ025</b>
<i>Description</i>	<i>In A</i>	<i>Cat. ref.</i>	<i>Cat. ref.</i>
		3P	4P
<b>Terminal cover</b>	125A to 200A,	<b>HZC201</b>	<b>HZC202</b>
	250A to 400A	<b>HZC203</b>	<b>HZC204</b>
	630A	<b>HZC205</b>	<b>HZC206</b>
	800A	<b>HZ036</b>	<b>HZ046</b>
	1250A to 1600A	<b>HZ037</b>	<b>HZ047</b>



**Description**

The range of enclosed FCS have been designed to match the TP&N range of distribution boards. The number of enclosure sizes have been optimized, to ensure that the installation is easy and uniform. The FCS products are designed to protect and isolate individual circuits. All handles can be padlocked in the off position. Extension boxes are available for extra cabling space.

Operation is through a door operated rotary handle.

**Note**

Maximum rate fuse links are fitted in all fuse combination switches.

**Electrical specification**

Tested and complies to  
IEC 60 497-3  
LBS Sequence 1 & 3  
FCS Sequence 1 & 4

**Electrical Supply**

415V~AC Rating AC23  
(100A~AC22A)

**Mechanical specification**

Material 1.2mm CR4 Steel  
Powder Coated RAL 9002  
IP40

**Devices & accessories**

SPSN 20 - 100A ( 4 ratings)  
TP & N 20 - 800A (12 ratings)  
TPSN 20 - 800A (12 ratings)



JFD306U

Description	In A	Utilisation category	Fuse type	Cat. ref.
Single pole switched neutral	20A	AC23A	A1	JFB202U
	32A	AC23A	A1	JFB203U
	63A	AC23A	A2-A3	JFD206U
	100A	AC22A	A4	JFE210U
Triple pole and neutral	20A	AC23A	A1	JFB302U
	32A	AC23A	A1	JFB303U
	63A	AC23A	A2-A3	JFD306U
	100A	AC22A	A4	JFE310U
	125A	AC23A	B1-B2	JFG312U
	160A	AC23A	B1-B2	JFG316U
	200A	AC23A	B1-B2	JFG320U
	250A	AC23A	B1-B3	JFG325U
	315A	AC23B	B1-B3	JFH331U
	400A	AC23B	B1-B4	JFH340U
	630A	AC23B	C1-C2	JFI363U
	800A	AC23B	C1-C3	JFI380U
Triple pole switched neutral	20A	AC23A	A1	JFB402U
	32A	AC23A	A1	JFB403U
	63A	AC23A	A2-A3	JFD406U
	100A	AC22A	A4	JFE410U
	125A	AC23A	B1-B2	JFG412U
	160A	AC23A	B1-B2	JFG416U
	200A	AC23A	B1-B2	JFG420U
	250A	AC23A	B1-B3	JFG425U
	315A	AC23B	B1-B3	JFH431U
	400A	AC23B	B1-B4	JFH440U
	630A	AC23B	C1-C2	JFI463U
	800A	AC23B	C1-C3	JFI480U
Cable extension boxes triple pole and triple pole switched neutral	125A, 160A, 200A, 250A			JZA701
	315A, 400A			JZA702
	630A, 800A			JZA703
Auxiliary contact 1AC type NO 1AC type NC				HZF301
				HZF302
Description	In A	Cat. ref.	Cat. ref.	Cat. ref.
		2P	3P	4P
Terminal cover	100A	HZF201	HZF202	HZF203
	125A, 160A,	-	HZF202	HZF203
	200A to 400A	-	HZF204	HZF205
	630A to 800A	-	HZF206	HZF207

Technical characteristics

Surface mounting	Insulation Voltage : 690 VAC	Removable pre punched top and bottom glandplates
1.2 mm thickness sheet steel	Direct cable connection for MCCBs, Neutral and Earth terminal up to 125A. For higher ratings neutral bar with bolts and nuts as standard	Dual knockouts
Epoxy Powder coated RAL 9002 colour		Enough cabling space
Operating voltage : 127/220/415V AC 50/60Hz	Provision for Padlock	MCCBs are calibrated at 50 Deg Centigrade

Designation

Cat. Ref.

Enclosed circuit breaker fitted with MCCB

ECB fitted with MCCB X160 3P 18kA 63A	MH1253S2HDA063Z
ECB fitted with MCCB X160 3P 18kA 100A	MH1253S2HDA100Z
ECB fitted with MCCB X160 3P 18kA 125A	MH1253S2HDA125Z
ECB fitted with MCCB X160 3P 25kA 63A	MH1253S2HHA063Z
ECB fitted with MCCB X160 3P 25kA 100A	MH1253S2HHA100Z
ECB fitted with MCCB X160 3P 25kA 125A	MH1253S2HHA125Z
ECB fitted with MCCB X160 3P 40kA 63A	MH1253S2HNA063Z
ECB fitted with MCCB X160 3P 40kA 100A	MH1253S2HNA100Z
ECB fitted with MCCB X160 3P 40kA 125A	MH1253S2HNA125Z
ECB fitted with MCCB X250 3P 25kA 160A	MH2503S2HHB160Z
ECB fitted with MCCB X250 3P 25kA 200A	MH2503S2HHB200Z
ECB fitted with MCCB X250 3P 25kA 250A	MH2503S2HHB250Z
ECB fitted with MCCB X250 3P 40kA 160A	MH2503S2HNB160Z
ECB fitted with MCCB X250 3P 40kA 200A	MH2503S2HNB200Z
ECB fitted with MCCB X250 3P 40kA 250A	MH2503S2HNB250Z
ECB fitted with MCCB h400 3P 50kA 400A	MH4003S2HND400U
ECB fitted with MCCB h630 3P 50kA 630A	MH6303S2HND630U

Note:

The above are the standard ratings of MCCBs. Incase any other ratings are required add the MCCB reference to the board reference.  
For Eg : If x160 frame,3P,18KA, 40A MCCB required the cat reference will be MH1253S2HDA040Z.



**Technical characteristics:**

- Standards: IEC 60439
- IP rating: IP55 / 65 as per IEC 529
- insulation voltage: 400V AC
- colour: RAL 7035 light grey
- mechanical impact resistance:
  - enclosures < 12 - IK07
  - enclosures > 12 - IK08
- Reversible doors - for enclosures > 12 modules

- supplied with earth and neutral terminals
- Distance between rails
  - 12 mod. wide enclosures - 125 mm
  - 18 mod. wide enclosures - 150 mm
- Metric knock outs on top and bottom
- Transparent door for all enclosures sizes



VE218L

<i>Designation</i>	<i>Dimension (H x W x D)</i>	<i>Cat. Ref.</i>
1 Row, 2 + 1 modules	175 x 111 x 93	<b>VE103L</b>
1 Row, 4 + 2 modules	190 x 165 x 113	<b>VE106L</b>
1 Row, 8 + 2 modules	210 x 237 x 114	<b>VE110L</b>
1 Row, 12 modules	302 x 310 x 151	<b>VE112L</b>
2 Row, 24 modules	427 x 310 x 151	<b>VE212L</b>
3 Row, 36 modules	552 x 310 x 151	<b>VE312L</b>
4 Row, 48 modules	677 x 310 x 151	<b>VE412L</b>
1 Row, 18 modules	302 x 418 x 151	<b>VE118L</b>
2 Row, 36 modules	452 x 418 x 151	<b>VE218L</b>
3 Row, 54 modules	602 x 418 x 151	<b>VE318L</b>

## Golf enclosures

**Technical characteristics:**





- Golf enclosures are available in surface and flush mounting 1 - 3 rows, 4 to 54 modules.
- Enclosures are of insulating material coloured RAL 9010.
- Fixed DIN rail for devices with shoulder measurement of 47mm.
- Distance between rails 125mm.

- Door opens up to 180°.
- Surface mounted enclosures are available with opaque or transparent doors.
- Key lock optional.
- IP40





VS212TF

<i>Designation</i>	<i>Characteristics</i>	<i>Plain door cat. ref.</i>	<i>Transparent door cat. ref.</i>
<b>Surface mounting</b>	1 row, 4 modules	<b>VS104PF</b>	<b>VS104TF</b>
	1 row, 8 modules	<b>VS108PF</b>	<b>VS108TF</b>
	1 row, 12 modules	<b>VS112PF</b>	<b>VS112TF</b>
	1 row, 18 modules	<b>VS118PF</b>	<b>VS118TF</b>
	1 row, 22 modules	<b>VS122PF</b>	<b>VS122TF</b>
	2 rows, 24 modules	<b>VS212PF</b>	<b>VS212TF</b>
	2 rows, 36 modules	<b>VS218PF</b>	<b>VS218TF</b>
	3 rows, 36 modules	<b>VS312PF</b>	<b>VS312TF</b>
	3 rows, 54 modules	<b>VS318PF</b>	<b>VS318TF</b>
	4 rows, 72 modules	<b>VS418PF</b>	<b>VS418TF</b>
<b>Flush mounting</b>	1 row, 4 modules	<b>VF104PF</b>	<b>VF104TF</b>
	1 row, 8 modules	<b>VF108PF</b>	<b>VF108TF</b>
	1 row, 12 modules	<b>VF112PF</b>	<b>VF112TF</b>
	1 row, 18 modules	<b>VF118PF</b>	<b>VF118TF</b>
	1 row, 22 modules	<b>VF122PF</b>	<b>VF122TF</b>
	2 rows, 24 modules	<b>VF212PF</b>	<b>VF212TF</b>
	2 rows, 36 modules	<b>VF218PF</b>	<b>VF218TF</b>
	3 rows, 36 modules	<b>VF312PF</b>	<b>VF312TF</b>
	3 rows, 54 modules	<b>VF318PF</b>	<b>VF318TF</b>
	4 rows, 72 modules	<b>VF418PF</b>	<b>VF418TF</b>


	Type		Prong			Fork	Section mod.			Cat. Ref.
			In/A	mm <sup>2</sup>	Width		In/A	mm <sup>2</sup>	Width	
 KB163P	1 Pole	Brown insulated	63A	10	13	KB163P				
		Blue insulated	63A	10	13	KB163N				
							63A	10	56	KD163B
							80A	16	56	KD180B
			100A	20	57	KB190B	100A	20	56	KD190B
 KB190C	1P end caps					KB190C				
						KZ021				KZN021
		2 Pole	63A	10	12	KB263A				
			63A	10	24	KB263C				
			80A	16	56	KB280B	63A	10	56	KD263B
 KD263B	2P end caps					KZ022	80A	16	56	KDN280B
										KZN023
		3 Pole	63A	10	12	KB363A				
			63A	10	57	KB363B	63A	10	57	KD363B
			63A	10	24	KB363C				
 KD363B	3P end caps		80A	16	12	KB380A				
			80A	16	57	KB380B	80A	16	57	KD380B
						KZ023A				
		4 Poles	63A	10	12	KB463A				
			63A	10	24	KB463C				
	4P end caps						63A	10	56	KD463B
			80A	16	12	KB480A				
			80A	16	56	KB480B	80A	16	56	KDN480B
						KZ024				KZN024

Note : all busbars grey insulated unless otherwise mentioned

Brass terminals

	Connections mm2	Terminals with support		Phase	Terminals w/o support Bare
		Neutral	Earth		
 K151	2x16 + 2x10			KM04L	K140
	4x16 + 4x10			KM08L	
	3x16 + 4x10	KM07N	KM07E	KM07L	K142
	5x16 + 5x10	KM10A	KM10B	KM10C	K143
	5x16 + 6x10	KM11N	KM11E	KM11L	K144
 KM10B	2x16 + 8x10	KM10N	KM10E	KM10L	K145
	6x16 + 7x10	KM13N	KM13E		K148
	1x25 + 5x16 + 5x10		KM11B		K151
	1x25 + 8x16 + 8x10	KM17N	KM17E		K156
	1x25 + 11x16 + 13x10	KM25N	KM25E		K158
	1x25 + 8x16 + 29x10				K159
	1x25 + 16x16 + 61x10				K160
	1x25 + 33x16 + 129x10				K162


Supports and Rail Clips available



Cat. Ref.	Dimensions				
	H	W	D	H1	W1
Surface					
VT04SM	231	214	70	226	208
VT06SM	231	250	70	226	244
VT08SM	231	286	70	226	280
VT10SM	231	322	70	226	316
VT12SM	231	358	70	226	352
VT16SM	231	430	70	226	424


Flush					
VT04FM	251	234	70	226	208
VT06FM	251	270	70	226	244
VT08FM	251	306	70	226	280
VT10FM	251	342	70	226	316
VT12FM	251	378	70	226	352
VT16FM	251	450	70	226	424

Consumer unit without busbar




Cat. Ref.	Dimensions				
	H	W	D	H1	W1
Surface					
VT04MS/PNS/TS	253	245	93	250	242
VT08MS/PNS/TS	253	316	93	250	313
VT12MS/PNS/TS	253	387	93	250	384
VT16MS/PNS/TS	253	458	93	250	456
VT20MS/PNS/TS	253	529	93	250	527

Flush					
VT04MF/PNF/TF	253	245	93	220	206
VT08MF/PNF/TF	253	316	93	220	277
VT12MF/PNF/TF	253	387	93	220	348
VT16MF/PNF/TF	253	458	93	220	420
VT20MF/PNF/TF	253	529	93	220	491




Cat. Ref.	Dimensions				
	H	W	H1	W1	D1
<b>Surface</b>					
DR16S	325	405	320	400	110
DR32S	475	405	470	400	110
DR48S	625	405	620	400	110
DR64S	775	405	770	400	110
DR80S	925	405	920	400	110
DR96S	1075	405	1070	400	110
<b>Flush</b>					
DR16F	350	430	320	400	110
DR32F	500	430	470	400	110
DR48F	650	430	620	400	110
DR64F	800	430	770	400	110
DR80F	950	430	920	400	110
DR96F	1110	430	1070	400	110

TPN 125 type B distribution boards




Cat. Ref.	Dimensions					
	H	W	D	H1	W1	D1
<b>Surface</b>						
JK1B04S2	495	405	115	490	400	110
JK1B06S2	555	405	115	550	400	110
JK1B08S2	605	405	115	600	400	110
JK1B10S2	660	405	115	655	400	110
JK1B12S2	715	405	115	710	400	110
JK1B14S2	770	405	115	765	400	110
JK1B16S2	820	405	115	815	400	110
JK1B18S2	940	405	115	935	400	110
JK1B24S2	1105	405	115	1100	400	110
<b>Flush</b>						
JK1B04F2	520	430	115	490	400	110
JK1B06F2	580	430	115	550	400	110
JK1B08F2	630	430	115	600	400	110
JK1B10F2	685	430	115	655	400	110
JK1B12F2	740	430	115	710	400	110
JK1B14F2	795	430	115	765	400	110
JK1B16F2	845	430	115	815	400	110
JK1B18F2	965	430	115	935	400	110
JK1B24F2	1130	430	115	1100	400	110




Cat. Ref.	Dimensions					
	H	W	D	H1	W1	D1
Surface						
JK1B022S2	555	445	115	550	440	110
JK1B042S2	610	445	115	605	440	110
JK1B044S2	665	445	115	660	440	110
JK1B062S2	665	445	115	660	440	110
JK1B064S2	720	445	115	715	440	110
JK1B066S2	775	445	115	770	440	110
JK1B082S2	720	445	115	715	440	110
JK1B084S2	775	445	115	770	440	110
JK1B086S2	830	445	115	825	440	110
JK1B088S2	885	445	115	880	440	110
JK1B104S2	935	445	115	930	440	110
Flush						
JK1B022F2	580	470	115	550	440	110
JK1B042F2	635	470	115	605	440	110
JK1B044F2	690	470	115	660	440	110
JK1B062F2	690	470	115	660	440	110
JK1B064F2	745	470	115	715	440	110
JK1B066F2	800	470	115	770	440	110
JK1B082F2	745	470	115	715	440	110
JK1B084F2	800	470	115	770	440	110
JK1B086F2	855	470	115	825	440	110
JK1B088F2	910	470	115	880	440	110
JK1B104F2	960	470	115	930	440	110






Cat. Ref.	Dimensions					
	H	W	D	H1	W1	D1
Surface						
JK2B04S2	655	445	115	650	440	110
JK2B06S2	705	445	115	700	440	110
JK2B08S2	760	445	115	755	440	110
JK2B10S2	815	445	115	810	440	110
JK2B12S2	865	445	115	860	440	110
JK2B14S2	920	445	115	915	440	110
JK2B16S2	975	445	115	970	440	110
JK2B18S2	1030	445	115	1025	440	110
JK2B24S2	1195	445	115	1190	440	110
Flush						
JK2B04F2	680	470	115	650	440	110
JK2B06F2	730	470	115	700	440	110
JK2B08F2	785	470	115	755	440	110
JK2B10F2	840	470	115	810	440	110
JK2B12F2	890	470	115	860	440	110
JK2B14F2	945	470	115	915	440	110
JK2B16F2	1000	470	115	970	440	110
JK2B18F2	1055	470	115	1025	440	110
JK2B24F2	1220	470	115	1190	440	110

TPN Board Accessories




Cat. Ref.	Dimensions					
	H	W	D	H1	W1	D1
JK1E01S	275	405	115	269	400	108
JK2E01S	275	445	115	269	440	108
JK1E01F	300	430	115	269	400	108
JK2E01F	300	470	115	269	440	108
JK1E16S	275	405	115	269	400	108
JK1E32S	425	405	115	420	400	108
JK1E48S	655	405	115	650	400	108
JK2E16S	275	445	115	270	440	108
JK2E32S	425	445	115	420	440	108
JK2E48S	575	445	115	570	440	108
JK1E16F	300	430	115	269	400	108
JK1E32F	450	430	115	419	400	108
JK1E48F	600	430	115	569	400	108
JK2E16F	300	470	115	269	440	108
JK2E32F	450	470	115	419	440	108
JK2E48F	600	470	115	569	440	108




Cat. Ref.	Dimensions		
	H	W	D
Surface mounted			
JN2B00002S2	700	615	160
JN2B00004S2	775	615	160
JN2B00006S2	850	615	160
JN2B00008S2	925	615	160
JN2B00010S2	1000	615	160
JN2B00012S2	1115	615	160
JN2B00016S2	1375	615	160
JN2B00002S3	860	615	160
JN2B00004S3	935	615	160
JN2B00006S3	1010	615	160
JN2B00008S3	1085	615	160
JN2B00010S3	1160	615	160
JN2B00012S3	1275	615	160
JN2B00016S3	1535	615	160

Invicta 400A panel board




Cat. Ref.	Dimensions		
	H	W	D
Surface mounted			
JN4B00004S2	930	690	200
JN4B00006S2	1005	690	200
JN4B00008S2	1080	690	200
JN4B00010S2	1155	690	200
JN4B00012S2	1230	690	200
JN4B00016S2	1380	690	200
JN4B00202S2	960	846	200
JN4B00204S2	1035	846	200
JN4B00206S2	1110	846	200
JN4B00208S2	1185	846	200
JN4B00210S2	1260	846	200
JN4B00214S2	1410	846	200




Cat. Ref.	Dimensions		
	H	W	D
Surface mounted			
JN4B00004S3	1090	690	200
JN4B00006S3	1165	690	200
JN4B00008S3	1240	690	200
JN4B00010S3	1315	690	200
JN4B00012S3	1390	690	200
JN4B00016S3	1540	690	200
JN4B00202S3	1120	846	200
JN4B00204S3	1195	846	200
JN4B00206S3	1270	846	200
JN4B00208S3	1345	846	200
JN4B00210S3	1420	846	200
JN4B00214S3	1570	846	200

Invicta 630 / 800A panel boards



Cat. Ref.	Dimensions		
	H	W	D
Surface			
JN8B00004S2	1035	846	200
JN8B00006S2	1110	846	200
JN8B00008S2	1215	846	200
JN8B00010S2	1320	846	200
JN8B00012S2	1410	846	200
JN8B00016S2	1620	846	200
JN8B00202S2	1065	846	200
JN8B00204S2	1140	846	200
JN8B00206S2	1215	846	200
JN8B00208S2	1320	846	200
JN8B00210S2	1410	846	200
JN8B00214S2	1560	846	200
JN8B00402S2	1170	846	200
JN8B00404S2	1245	846	200
JN8B00406S2	1350	846	200
JN8B00408S2	1440	846	200
JN8B00410S2	1650	846	200
JN8B00606S2	1485	846	200
JN8B00608S2	1620	846	200
JN8B00400S2	1095	846	200
JN8B00600S2	1200	846	200
JN8B00800S2	1305	846	200
JN8B01000S2	1410	846	200
JN8B01200S2	1515	846	200
JN8B01400S2	1725	846	200




Cat. Ref.	Dimensions		
	H	W	D
<b>Surface</b>			
JN8B00202S3	1225	846	200
JN8B00204S3	1300	846	200
JN8B00206S3	1375	846	200
JN8B00208S3	1480	846	200
JN8B00210S3	1570	846	200
JN8B00214S3	1720	846	200

Invicta panel board accessories



Cat. Ref.	Dimensions		
	H	W	D
<b>Surface</b>			
JN2E01S	303	615	160
JN2E02S	179	615	160
JN2E20S	303	615	160
JN4E01S	303	690	200
JN4E02S	179	690	200
JN4E24S	303	690	200
JN8E01S	303	846	200
JN8E02S	179	846	200
JN8E32S	453	846	200


Enclosed circuit breaker



Cat. Ref.	Dimensions		
	H	W	D
MH1253S2	400	245	112
MH2503S2	630	350	112
MH4003S2	650	370	152
MH6303S2	1010	600	152

Vector IP65 enclosures

VE 212L - 2 rows 24




Dimensions


References		Enclosure sizes			Wall box	
		B	A	H	E	F
VE103L	3	1	111	175	-	147
VE106L	6	1	165	190	108	158
VE110L	10	1	237	210	180	173
VE112L	12	1	310	302	230	155
VE212L	24	2	310	427	230	280
VE312L	36	3	310	552	230	405
VE412L	18	4	310	677	230	550
VE118L	18	1	418	302	338	155
VE218L	36	2	418	452	338	305
VE318L	54	3	418	602	338	455

Connection assembly

mounting on insulating support at both end of the chassis  
additional connection assembly : VZ 403 or VZ 428  
insulated terminal VZ 743




enclosure reference	knock outs high and low	side	supplied cable bushes
VE103L	2 x M20	-	3 x M20
VE106L	1 x M20 + 1 x M25 + 1 x M20/32	2 x 16	2 x M20 + 2 x M25 + 1 x M32
VE110L	1 x M20/32 + 1 x M25 + 3 x M20	2 x 16	4 x M20 + 2 x M25 + 1 x M32
VE112L	2 x M20/32/40 + 2 x M 25/32 + 3 x M25 + 6 x M20	2 x 21	10 x M20 + 2 x M25 + 1 x M32
VE118L	1 x M20/40/50 + 2 x M20/32 + 12 x M25 + 2 x M20	2 x 21	8 x M20 + 10 x M25 + 1 x M32
VE212L	2 x M20/32/40 + 2 x M25/32 + 3 x M25 + 6 x M20	3 x 21	14 x M20 + 4 x M25 + 1 x M32
VE218L	1 x M20/40/50 + 2 x M20/32 + 12 x M25 + 2 x M20	3 x 21	8 x M20 + 14 x M25 + 1 x M32
VE312L	2 x M20/32/40 + 2 x M25/32 + 3 x M25 + 6 x M20	4 x 21	14 x M20 + 10 x M25 + 2 x M32
VE318L	1 x M20/40/50 + 2 x M20/32 + 12 x M25 + 2 x M20	4 x 21	8 x M20 + 18 x M25 + 2 x M32
VE412L	2 x M20/32/40 + 2 x M25/32 + 3 x M25 + 6 x M20	5 x 21	14 x M20 + 10 x M25 + 2 x M32



Ref.		Dimension		Wall fixation		
		A	H	E	F	G
VS104...	1 row 4 ■	137,5	183,5	101	68	58
VS108...	2 row 8 ■	209,5	183,5	173,5	68	58
VS112...	1 row 12 ■	281,5	251,5	221,5	135,5	58
VS212...	2 row 12 ■	281,5	376,5	221,5	260,5	58
VS312...	3 row 12 ■	281,5	500	221,5	385,5	58
VS412...	4 row 12 ■	281,5	646,5	221,5	491	78
VS118...	1 row 18 ■	389,5	251,5	329,5	135,5	58
VS218...	2 row 18 ■	389,5	376,5	329,5	260,5	58
VS318...	3 row 18 ■	389,5	500	329,5	385,5	58
VS418...	4 row 18 ■	389,5	646,5	329,5	491	78
VS122...	1 row 22 ■	461,5	251,5	401,5	135,5	58

■ - mod

Golf flush mounted enclosure  
VF series



Ref.		Dimension // mm			
		Frame		Wall niche	
		A	H	E	F
VF104...	1 row 4 ■	204	225	170	189
VF108...	2 row 8 ■	275	225	242	189
VF112...	1 row 12 ■	352	293	318	257
VF212...	2 row 12 ■	352	418	318	382
VF312...	3 row 12 ■	352	543	318	507
VF412...	4 row 12 ■	352	688	318	652
VF118...	1 row 18 ■	460	293	426	257
VF218...	2 row 18 ■	460	418	426	382
VF318...	3 row 18 ■	460	543	426	507
VF418...	4 row 18 ■	460	688	426	652
VF122...	1 row 22 ■	532	293	498	257

For the wall niche, these dimensions are minimal.

■ - mod



